


EZ-LIGHT® S22L General Purpose Indicators



Datasheet

DC-Operated LED Indicators with One, Two, or Three Colors



- Up to three independent colors in one unit
- Translucent face appears gray when off to avoid false indication
- M12 Euro connector models available for plug and play indication
- Wide 180° field of view
- Wide 10 V dc to 30 V dc operating range allows for use in battery powered mobile applications
- Available with PNP or NPN input, depending on model
- IP69K rated to withstand harsh wash-down environments
- Wide operating range of -40 °C to +50 °C (-40 °F to +122 °F)
- Daylight visible models with a clear cover and more focused light output provide greater visibility in high ambient light conditions

Models

Table 1: Standard Models

Family	Color 1	Color 2	Color 3	Input	Connector
S22L	G	R	Y	P	Q
MODEL KEY	G = Green R = Red Y = Yellow B = Blue W = White O = Orange T = Turquoise V = Violet M = Magenta X = No color in this position			P = PNP N = NPN	Q = 4 pin Euro QD Blank = 2 meter cable QP = Euro Pigtail QD T = 4 screw terminals

Table 2: Daylight Visible Models

Family	Color 1	Color 2	Color 3	Input	Connector
S22DL	G	R	Y	P	Q
MODEL KEY	G = Green R = Red Y = Yellow B = Blue W = White O = Orange X = No color in this position			P = PNP N = NPN	Q = 4 pin Euro QD Blank = 2 meter cable QP = Euro Pigtail QD T = 4 screw terminals

Example Model	Indicators	Input	Connector Type
S22LGRYP	Green, Red, Yellow	PNP	2 m cable
S22LGXXPQ	Green	PNP/NPN	4-pin Euro QD
S22LGRXPQP	Green, Red	PNP	Euro Pigtail QD
S22LGRYPT	Green, Red, Yellow	PNP	4 screw terminals




Note: Single color models should be ordered as PNP models but can be wired for either PNP or NPN input.


Wiring Diagrams

Multi Color Wiring

NPN



PNP



- 1 = Brown
- 2 = White
- 3 = Blue
- 4 = Black
- 5 = Gray


- C1 = Color 1
- C2 = Color 2
- C3 = Color 3

Gray Wire not used in K30 Terminal models




Single Color Wiring

NPN



PNP



Specifications

Supply Voltage and Current

10 V DC to 30 V DC at 25 mA max. per LED color

Indicators

LEDs are independently selected; 1, 2, or 3 colors, depending on model. For other colors/combinations, contact Factory for availability

Standard Models: Entire translucent dome provides even indication viewable from over 180 degrees

Daylight Visible Models: Clear dome and more focused light provides even brighter indication when used in high ambient light areas

Indicator Response Time

Indicator ON/OFF: 1 ms max

Indicator Characteristics

Color	Dominant Wavelength (nm) or Color Temperature (CCT)	Color Coordinates ¹		Lumen Output (Typical at 25 °C)	
		X	Y	S22L	S22DL
		S22L Only			
Green	520-535 nm	-	-	4.1	2.3
Red	620-630 nm	-	-	1.1	1.4
Yellow	585-595 nm	-	-	0.8	1.2
Blue	465-475 nm	-	-	0.6	0.6
Orange	600-615 nm	-	-	4.0	4.0
White	5665-9000 K	-	-	0.8	0.9
Turquoise	-	0.19	0.34	2.4	NA ²
Violet	-	0.21	0.11	0.5	NA ²
Magenta	-	0.35	0.15	0.5	NA ²

Environmental Rating

Rated IEC IP67, and IP69K per DIN 40050-9. Cabled models meet DIN IP69K if the cable is protected from high-pressure spray. Indicator side of terminal models meet IEC IP67, and IP69K per DIN 40050-9 when installed in an enclosure. Screw connection points meet IEC IP00. Meets UL Type 4X and UL Type 13 when mounted in a UL Type 4X or Type 13 enclosure.

Required Overcurrent Protection



WARNING: Electrical connections must be made by qualified personnel in accordance with local and national electrical codes and regulations.

Overcurrent protection is required to be provided by end product application per the supplied table.

Overcurrent protection may be provided with external fusing or via Current Limiting, Class 2 Power Supply.

Supply wiring leads < 24 AWG shall not be spliced.

For additional product support, go to www.bannerengineering.com.

Supply Wiring (AWG)	Required Overcurrent Protection (Amps)
20	5.0
22	3.0
24	2.0
26	1.0
28	0.8
30	0.5

Construction

UV stabilized polycarbonate housing
PBT mounting nut max torque 2.3 N·m (20 lbf-in)
Nitrile sealing washer

Connections

Integral 4-pin M12/Euro-style male quick disconnect, 150 mm (5.9 in) PVC cable with QD, or 4-wire, 2 m (6.5 ft) PVC integral cable, 4 color-coded screw terminals for up to 16 AWG wire, depending on model, screw terminal max. torque 0.11 N·m (1.0 lbf-in)


Operating Conditions

-40 °C to +50 °C (-40 °F to +122 °F)
Limited to one color on at a time

Certifications






Dimensions



¹ Refer to CIE 1931 chromaticity diagram or color chart, to show equivalent color with indicated color coordinates.
² Colors not available in this model.

Cordsets


4-Pin Threaded M12/Euro-Style Cordsets—Single Ended				
Model	Length	Style	Dimensions	Pinout (Female)
MQDC-406	1.83 m (6 ft)	Straight		 <p>1 = Brown 2 = White 3 = Blue 4 = Black</p>
MQDC-415	4.57 m (15 ft)			
MQDC-430	9.14 m (30 ft)			
MQDC-450	15.2 m (50 ft)	Right-Angle		
MQDC-406RA	1.83 m (6 ft)			
MQDC-415RA	4.57 m (15 ft)			
MQDC-430RA	9.14 m (30 ft)			
MQDC-450RA	15.2 m (50 ft)			

Brackets

All measurements are listed in millimeters, unless noted otherwise.

SMB22A


- Right-angle bracket with curved slot for versatile orientation
- 12-ga. stainless steel
- Mounting hole for 22 mm sensor



Hole center spacing: A to B = 26.0
Hole size: A = ø 4.6, B = 4.6 x 16.9, C = 22.2

SMB22FVK


- V-clamp, flat bracket and fasteners for mounting to pipe or extensions
- Clamp accommodates 28 mm diameter tubing or 1 in. square extrusions
- 22 mm hole for mounting sensor



Hole size: A = ø 22.5

SMB22RAVK


- V-clamp, right-angle bracket and fasteners for mounting to pipe or extensions
- Clamp accommodates 28 mm diameter tubing or 1 in. square extrusions
- 22 mm hole for mounting sensor



Hole size: A = ø 22.5

SMBAMS22P


- Flat SMBAMS series bracket with 22 mm hole for mounting sensors
- Articulation slots for 90+° rotation
- 12-ga. (2.6 mm) cold-rolled steel



Hole center spacing: A = 26.0, A to B = 13.0
Hole size: A = 26.8 x 7.0, B = ø 6.5, C = ø 22.5

SMBAMS22RA

- Right-angle SMBAMS series bracket with 22 mm hole for mounting sensors
- Articulation slots for 90+° rotation
- 12-ga. (2.6 mm) cold-rolled steel



Hole center spacing: A = 26.0, A to B = 13.0
Hole size: A = 26.8 x 7.0, B = ø 6.5, C = ø 22.5

Banner Engineering Corp. Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.