

DIELECTRIC WITHSTANDING VOLTAGE: AC 1200 R.M.S. INSULATION RESISTANCE: 1000 mohms MINIMUM AT 500V DC CONTACT RESISTANCE: 30 mOHMS MAXIMUM OPERATING TEMPERATURE: -55°C TO +125°C

**ELECTRICALS:** 

**CONTACT CURRENT RATING: 5 AMPS** 

ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.  SCALE:  SCALE:  1:1  1  1  REV 2	MOLCOMP		DWG NO. 110-XXX-103-001				
ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE CUECUED.	NIA	rComn		SHEET	0F 1 1		1
ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED SHALL NOT BE REPRODUCED.	Ø	SHALL NOT BE REPRODUCED, COPIED OF USED AS THE BASIS FOR THE	CHECKED:		DATE:		
THESE DRAWINGS AND SPECIFICATIONS DRAWN: DATE:					DATE:	9-17-98	