



NOTES:

1. MATERIALS: LCP, INHERENTLY FLAME-RESISTANT UL 94 V-0
2. PLATING (MIN.): 3.84μm BRIGHT NICKEL OVER 2.54μm COPPER UNDERPLATE.
3. PLUG CAN BE USED WITH ALL CXP CONNECTOR ASSEMBLIES.
4. PART TO CONFORM TO THE MOLEX COSMETIC SPECIFICATION PS-45499-002; SURFACES TO BE CLASS "B".

1708461002	PLATED
1708461001	NON-PLATED
MATERIAL NO.	DESCRIPTION

NOTE 1: UL RATING EC NO: UCP2013-5382 DRWNG: PRATT 2013/06/12 CHKD: MBANAKIS 2013/06/12 APPR: MBANAKIS 2013/06/13	QUALITY SYMBOLS ▽=0 ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
		4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± 0.25 ± --- 1 PLACE ± --- ± ---	mm INCH	DRAWN BY JLONG	DATE 2011/03/02	TITLE IPASS+ CXP EMI / STD DUST PLUG			
		ANGULAR ± 1 °		CHECKED BY JLONG	DATE 2011/03/02	APPROVED BY MBANAKIS			DATE 2011/03/14
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE CHART		MOLEX INCORPORATED			DOCUMENT NO. SD-170846-1000