



Scan the QR code and
visit the product page



Code	TK.LB.C0010.MEC	Safety level	Caution
Dimensions (H x L)	69 mm x 140 mm (2,7" x 5,5")	Version	Standard
Material	Base in anodized aluminum 0.5 mm thickness with white background and 3.5 mm holes on the edges	Temperatures ⁽¹⁾	-40°C/+100°C
Applications	Machinery and control panels. Indoor and outdoor locations		
Languages ⁽²⁾	Inglese		
Message ⁽³⁾	EN: Burn hazard. Hot surfaces. Do not touch. IT: Pericolo di ustione. Superfici calde. Non toccare.		
Certifications	c(UL)us Recognized - File#MH60136 (PDGQ2, PGDQ8)		
Standards of use	ANSI Z535, OSHA Art. 1910.145, NFPA 70 (NEC), NFPA 79, UL 508A, CSA C22.1 (CECode), CSA C22.2 No.286		
Standards Construction	ANSI Z535, UL 969, CSA C22.2 No.0.15, ISO 3864, RoHS		
Standard packaging	6 pz/pcs		

(1) For indoor and outdoor exposure with high humidity. UL certification is for maximum working temperatures of +100°C.

(2) Other languages may have different sizes and available upon request.

(3) The message and the image are shown in English language only.