


HC-D 7-AMLD-24/GR-OD

Order No.: 1684994

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1684994>

HEAVYCON panel mounting base D7, with single locking latch, height 24 mm, straight, aluminum, with aluminum protective cover, for male inserts

Commercial data	
GTIN (EAN)	
sales group	D011
Pack	10 pcs.
Customs tariff	85369010
Catalog page information	Page 509 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
09/27/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
General data	
Note	For contact inserts HC-D7, D8, A3, A4, B5, HS2-D7
Design	D7
Height	24 mm
Locking type	With single locking latch


Protective cover	Yes
Degree of protection	IP54 / IP65 with sealing screw
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Zinc die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Material lock	Steel, galvanized
Single locking latch material	Zinc-plated steel and passivated
Material, protective cover	Zinc
Length of the assembly cutout	21.5 mm
Width of the assembly cutout	21.5 mm

Accessories

Item	Designation	Description
Assembly		
1686229	HC-D 7-DS-IP65	Sealing screw, for IP65 protection

Diagrams/Drawings

Dimensioned drawing



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;