



21.6	17.2	52089-1619	16
20.6	16.2	52089-1519	15
15.6	11.2	52089-1019	10
13.6	9.2	52089-0819	8
12.6	8.2	52089-0719	7
10.6	6.2	52089-0519	5
B	A	MATERIAL NO.	極数 CKT.

- 注記 NOTES**
- △ CKT. NO. 1を基準に偶数番目のソルダーテール。
EVEN NUMBER SOLDER TAIL
 - △ CKT. NO. 1を基準に奇数番目のソルダーテール。
ODD NUMBER SOLDER TAIL
 - △ 接点部までの嵌合長さ。
LENGTH TO CONTACT POINT.
 - 4. 使用材料 MATERIAL
ハウジング : 66ナイロン, UL94V-0
HOUSING : 66NYLON, UL94V-0
アクチュエータ : ポリエステル, UL94V-0
ACTUATOR : POLYESTER, UL94V-0
ターミナル : リン青銅, ニッケル下地 錫・ピスマスメッキ
TERMINAL : PHOS-BRO. TIN-BISMUTM OVER NICKEL-PLATED
 - △ キングはソルダーテール△の両端のみに適用。
KINK APPLIES BOTH SIDE △ TERMINALS ONLY
 - 6. 本製品は 52089-** * 1.0 の鉛フリー品である。
THIS PRODUCT IS LEAD FREE OF 52089-** * 1.0.

REVISED EC NO: J2017-0269 IDRMNIGES 2016/11/17 CHKD: APPR: MSASAO 2016/12/26	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE MM ONLY	SCALE 10:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION													
	<table border="1"> <tr> <td>0.25 UNDER</td> <td>±</td> </tr> <tr> <td>0.25 OVER</td> <td>±</td> </tr> <tr> <td>0.5 OVER</td> <td>±</td> </tr> <tr> <td>1.0 OVER</td> <td>±0.2</td> </tr> <tr> <td>3.0 OVER</td> <td>±0.25</td> </tr> <tr> <td>30 OVER</td> <td>±0.3</td> </tr> <tr> <td>ANGULAR</td> <td>±3 °</td> </tr> </table>	0.25 UNDER	±	0.25 OVER	±	0.5 OVER	±	1.0 OVER	±0.2	3.0 OVER	±0.25	30 OVER	±0.3	ANGULAR	±3 °	DRAWN BY: J. SASAMO DATE: 2004/7/22 CHECKED BY: K. TOJO DATE: 2004/7/22 APPROVED BY: N. UKITA DATE: 2004/7/22 MATERIAL NO.	TITLE 1.0 FPC CONN ZIF R/A	
0.25 UNDER	±																	
0.25 OVER	±																	
0.5 OVER	±																	
1.0 OVER	±0.2																	
3.0 OVER	±0.25																	
30 OVER	±0.3																	
ANGULAR	±3 °																	
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION															

-LEAD FREE-
molex

DOCUMENT NO. SD-52089-001 SHEET NO. 1 OF 1