

# HIGH-PERFORMANCE LORA-ENABLED GATEWAY CARD FEATURING M2.COM INTERFACE

#### The Sentrius™ RG1xx-M2 LoRa-enabled concentrator

**card** combines Laird's long-standing expertise in optimized RF design with the emerging LoRaWAN ecosystem. The Sentrius RG1xx-M2 card enables OEMs to integrate a high-performance, certified LoRaWAN gateway interface to any Linux based platform. Laird's optimum hardware solution expands upon Semtech drivers and reference design for improved RF performance. Comprehensive integration and design services for a custom gateway are also available via Laird's dedicated Engineering Services team, as are qualified LoRa antenna solutions from Laird.



- Optimized RF performance Improvements over Semtech reference design for:-
  - Power variation over temperaturePerformance over frequency
- Superior TX Performance Up to +27dBm
- Standardized Interface M2 connector with compliance to M2.COM standard E type key.
- Comprehensive Certifications FCC, IC, CE

## Partner with Laird to create your own custom LoRa-enabled gateway

From embedded hardware, easy-to-connect antennas to expert integration services, Laird provides a comprehensive array of capabilities to build a customized LoRaWAN implementation, including:



#### LoRa-Equipped Concentrator card

Quickly add LoRaWAN capability to any Linuxbased Gateway design via standard M2.COM interface.



### **Product Development Services**

Laird is your partner for enclosure design, Linux driver implementation, FCC/IC/CE Certification testing, and more.



#### Antennas

Laird offers a family of high-gain omnidirectional antennas ideally suited for LoRa applications.

## **Application Areas**



Smart Metering and Remote Sensing



Industrial Automation/Monitoring and Control



Agricultural and Rural IoT / M2M Applications

### **Shared Specifications**

Category	Feature	Specification		
General Radio	Semtech Radios	SX1301 and SX1257 (x2)		
	<b>Reference</b> Design	Based on Semtech Rev 1.0 - SX1301 AP1		
Connectors	Connector Type	M2.COM E Key - http://www.m2com-standard.org/en-us		
	External Antenna	u.FL connector		
Power	Consumption	TX (max): RX (all channels): Idle: 440mA. 340mA 40mA		
Voltage	Input	5V (+/- 10%)		
RF Characteristics	Frequency Range	RG186-M2863 to 870 MHzRG191-M2902 to 928 MHz		
	RX sensitivity	Up to -140 dBm		
	Max RF Output Power	Up to +27 dBm		
Software	Host Interface	SPI		
	Driver Support	https://github.com/Lora-net/lora_gateway (Laird testing done with Linux)		
Temperature	Operating Range	-30 to +85		
Physical	Dimensions	75 x 53 x 3.8 mm		
	Weight	<11g		
Regulatory	Certifications	FCC / IC / CE		
Warranty		12 months		

### **Ordering Information**

RG186-M2	LoRaWAN Concentrator Card – M2.COM Interface (Europe)	Q2 2017
RG191-M2	LoRaWAN Concentrator Card – M2.COM Interface (N. America)	Q2 2017

### **Related Products**

#### Sentrius™ RM1xx - LoRa + BLE Certified Modules



LoRa Class 1 + Bluetooth Low Energy module with smartBASIC for automated / hostless operation. Now with Bluetooth Central Mode. www.lairdtech.com/products/rm1xx-series

### Sentrius™ RG1xx – LoRa-Enabled Gateway



LoRa Class 1, Bluetooth Low Energy and 802.11ac Wi-Fi, completing the end-to-end solution for your own private, custom LoRaWAN network. Coming Q2 2017

## Did You Know?

LSR, a Laird Business, is a leader in Wireless Product Development, offering true end-to-end solutions through its array of services & technical expertise



#### Design Services

- RF Hardware & Antenna Design
- Software/Firmware Development
  - Mobile App / Cloud Development
- Industrial Design

Mechanical Engineering

#### EMC Testing & Certification

- On-Site FCC/IC/CE/Giteki/RCM EMC Certification
- Wireless & Antenna Testing
- EMC Emissions Testing
- International Testing Services

To learn more about LSR visit: www.lsr.com

g Inte