


SPECIFICATION CONTROL DRAWING



MATERIALS

1. INSULATION SLEEVE: Heat shrinkable, transparent blue, radiation cross-linked polyvinylidene fluoride.
2. SOLDER PREFORM WITH FLUX:
 - SOLDER: TYPE Sn63 per ANSI J-STD-006.
 - FLUX: TYPE ROL1 per ANSI J-STD-004.

APPLICATION

1. This sleeve is designed to terminate 26 through 22 AWG wire connectors with tinned $\phi 0.64$ ($\phi 0.025$) pins, 5.08 (0.200) high.
2. Sleeve will recover to 0.76 (0.030) I.D. max.
3. This drawing forms part of Raychem Devices Specification Control Drawing D-711-03.

Raychem Interconnect <small>a division of tjco / Electronics</small> 300 Constitution Drive Menlo Park, CA 94025, USA		THERMOFIT DEVICES	TITLE : SOLDERSLEEVE STEPPED INSULATION For Burndy UPC Connector				
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. INCHES DIMENSIONS ARE BETWEEN BRACKETS.			DOCUMENT NO.: D-141-21				
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	ANGLES: N/A ROUGHNESS IN MICRON	Raychem reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application.	DCR NUMBER: D000588	REPLACES: N/A			
DRAWN BY: M. FORONDA	DATE: 02-Oct.-00	PROD. REV. F	DOC ISSUE: 1	SCALE: None	SIZE: A	SHEET: 1 of 1	

If this document is printed it becomes uncontrolled. Check for the latest revision.