



Main

Range	Square D X Series
Product or Component Type	TV + telephone socket
Device Application	Communication
Device presentation	Mechanism with fixing frame
Aesthetic name	X Series

Complementary

Connector Type	F connectors RJ11
Number of contact position	4
Number of contacts	4
Type of signal	DATA
Electrical circuit type	CATV Telephone
Number of gangs	1 gang
Mounting Mode	By screws
Device mounting	Flush
Material	Plastic strap Metal fixing frame
Color	Light almond
Surface Finish	Matte
Contacts material	Phosphor bronze with nickel plating
Width	1.46 in (37 mm)
Height	4.06 in (103 mm)
Depth	3.54 in (90 mm)
Quantity per Set	1 piece

Environment

Product Certifications	ETL verified
Standards	UL 1863

Ordering and shipping details

Category	09932-WD BASIC DEVICES
Discount Schedule	DE9
GTIN	785901550204
Nbr. of units in pkg.	1
Package weight(Lbs)	1.52 oz (43.0 g)
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.91 in (2.3 cm)
Package 1 width	1.46 in (3.7 cm)
Package 1 Length	4.06 in (10.3 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	17.18 oz (487.0 g)
Package 2 Height	2.76 in (7 cm)
Package 2 width	5.31 in (13.5 cm)
Package 2 Length	8.27 in (21 cm)
Unit Type of Package 3	CAR
Number of Units in Package 3	200
Package 3 Weight	22.80 lb(US) (10.34 kg)
Package 3 Height	17.32 in (44 cm)
Package 3 width	11.42 in (29 cm)
Package 3 Length	14.76 in (37.5 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: carbon black, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	2 years
----------	---------