

November 2018

Wireless Power Transfer

Small Rx (Receiving) Coil unit

WR303050-12F5-ID

Wireless Power Transfer

Small Rx coil unit

FEATURES

- O Receiving coils for Wireless Power Transfer.
- \bigcirc Flexible sheet type is used.
- Custom design is available based on each design requirements.
- O Halogen-free.

APPLICATION

29.6typ.(30.0max.)

.86typ. 94max

Smartphones, cellular phones, handheld mobile terminals, DSCs, and Wearable products.

SHAPE & DIMENSIONS

COMBINATION TABLE

	1W	2W	3W
Rx	WR121210-27M8-ID	WR202010-18M8-ID	WR303050-12F5-ID
Тx	WT151512-22F2-ID	WT202012-15F2-ID	WT303012-12F2-ID

30.0typ.(30.4max.) Solder coat 48.0typ.

Dimensions in mm

ELECTRICAL CHARACTERISTICS

CHARACTERISTICS SPECIFICATION TABLES

L x W dimensions	Thickness	Inductance [100kHz, 1Vrms]	Resistance [100kHz, 1Vrms]	Part No.	
(mm)	(mm)max.	(µH)	(Ω)		
30×29.6	0.94	8.23	0.28	WR303050-12F5-ID	

* Contact us for more information.

■ IC REFERENCE INFORMATION

IC	Manufacturer material name	Web
IDT	P9027LP-R	http://www.idt.com/products/power-management/wireless-charging-ics-wireless-power-ics/qi-compliant-wireless-power-transmitter-ics/ wp3w-rk-wireless-power-reference-solution-05w-3w-applications

O RoHS Directive Compliant Product: See the following for more details.https://product.tdk.com/info/en/environment/rohs/index.html

O Halogen-free: Indicates that CI content is less than 900ppm, Br content is less than 900ppm, and that the total CI and Br content is less than 1500ppm.

Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use. Please note that the contents may change without any prior notice due to reasons such as upgrading.

⊗TDK

Product compatible with RoHS directive Halogen-free

▲ Reminders

- Do not use or store in locations where there are conditions such as gas corrosion (salt, acid, alkali, etc.).
- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- O Fully caution, if metal piece contacted with top of coil surface then it could be danger of generated heat.
- Do not use for a purpose outside of the contents regulated in the delivery specifications.
- O The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.
 - The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.

If you intend to use the products in the applications listed below or if you have special requirements exceeding the range or conditions set forth in the each catalog, please contact us.

- (1) Aerospace/aviation equipment
- (2) Transportation equipment (cars, electric trains, ships, etc.)
- (3) Medical equipment
- (4) Power-generation control equipment
- (5) Atomic energy-related equipment
- (6) Seabed equipment
- (7) Transportation control equipment

- (8) Public information-processing equipment
- (9) Military equipment
- (10) Electric heating apparatus, burning equipment
- (11) Disaster prevention/crime prevention equipment
- (12) Safety equipment
- (13) Other applications that are not considered general-purpose applications