



**NOTES:**

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. THREADED INSERTS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
3. COLLARS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
4. JACK SCREWS: STEEL; NICKEL PLATED
5. CONNECTOR IS PART MARKED: 165X16949X CONEC ABC

RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

tolerance	ISO 2768-m				dim. in mm
date	name	drawn	21.01.15	Henneboel	
		appd.	21.01.15	Lehmenkühler	
		norm			
		d-old			
rev.	a	description	Original	<b>CONEC</b> <sup>®</sup>	
		date			

scale:	2:1 (5:1)	
material:	SEE NOTES	
title:	SCREEN CAP 50pos. for socket connector with jack screw	
dwg no:	16K1A3574	DIN-A3 sh: 1
part no:	165X16949X	