

Order No.	0478260000
Part designation	AST 1 6.3/2.8
Version	Special terminal, special connections, 2.5 mm²,
	Flat-blade connection, Polyamide, beige, TS 32
EAN	4008190003043
Qty.	50 pc(s).

Product notes

Note, technical data

Cable-lug connections should be fitted with insulating sleeves. 20 A with F 6.3 or 2 x F 2.8

Colour of insulating material beige
Connection direction top
End plate required Yes
Explosion-tested version "Ex e" No
Installation advice TS 32
Insulating material Polyamide
Levels cross-connected internally No

No. of identical terminals

No. of levels

No. of terminal strips per level

Open sides

1

No. of terminal strips per level

4

Open sides

Operating temperature range - 50 °C, + 100 °C
Product family SAK Series
Type of connection Plugged
Type of mounting Snap-on
UL 94 flammability rating of insulation material V2

Version Feed-through terminal

CSA rating data

Voltage (CSA) 300 V CSA current 16 A

Conductors for clamping (additional

No. of connections 4

Conductors for clamping (rated connection)

Clamping range, min. 0.5 mm²



Conductors for clamping (rated connection)	
Clamping range, max.	2.5 mm ²
Type of connection	Flat-blade connection
Connection direction	top
No. of connections	4
Flexible, min.	0.5 mm ²
Flexible, max.	2.5 mm²
Dimensions	
Width	6.5 mm
Height of lowest version	46 mm
Length	58 mm
Weight	11.96 g
TS 32 offset	26 mm
Other connections	
Cable-lug connection	Slotted
No. of connections	4
Rated cross-section spade connector 2.8 mm	1 mm ²
Rated cross-section spade connector 6.3 mm	2.5 mm²
Rating data	
Rated cross-section	2.5 mm ²
Rated voltage	500 V
Rated impulse voltage	6 kV
Rated current	20 A
Standards	IEC 60947-7-1 / IEC 61210
Current with max. conductor	20 A
Pollution severity	3
UL rating data	
Voltage (UL)	600 V

Approvals

Current (UL)

Approvals institutes



13 A











Classifications	
ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-31
eClass 5.0	27-14-11-31
eClass 5.1	27-14-11-31



Similar products

0266360000	AST 1 6.3	Special terminal, special connections, 2.5 mm ² , Flat-blade
		connection, Polyamide, beige, TS 32

