

P/N 1430-26-1-0500-0XX-1-TS

Conductor: Tinned Strands

Insulation: XLPVC



UL1430 XLPVC Wire 105°C 300V (26AWG)

| | |
|--|---|
| CONSTRUCTION: | Tinned Strands, copper conductor, 7/0.160mm strands. Overall Diameter=1.30+/-0.10mm Insulation Thickness: 0.38mm |
| CERTIFICATION & APPROVALS: | DUAL-RATED AWM: Can be used in USA and Canada UL Subject 758 UL FILE NO:E108485 CSA Standard CSA FILE NO:LL84687 Printed Markings: AWG 1430 VW-1 105°C 300V E108485-S ()AWG REI HSING CSA AWM I A 105° 300V LL84687 ()AWG FT1 -F- LF |
| PHYSICAL & ELECTRICAL PROPERTIES: | Rated Temperature: 105°C ~ -10°C Rated Voltage: 300V Insulation Potential Strength: 2000 VAC/min. Flexibility: XLPVC Insulation Maximum Conductor Resistance: 152 ohm/km Resistant to: Oil, hot & cold, lighter, flexing. |
| APPLICATIONS: | XLPVC Wire, pass VW-1 flame test Suitable for electric cookers, hair dryers, internal transformer coils, air-conditioners, lights fixture, electric ovens etc. |
| PACKAGING: | 500ft per reel. |
| ENVIRONMENTAL APPROVALS: | Conforms to all current RoHS directives as laid out in EU Directive 2011/65/EC. Current SGS reports for this wire are available upon request. |

P/N's & COLORS

| | | | | |
|----------------------------------|----------------------------------|-----------------------------------|-----------------------------------|---|
| 1430-26-1-0500-001-1-TS BLACK | 1430-26-1-0500-002-1-TS WHITE | 1430-26-1-0500-003-1-TS YELLOW | 1430-26-1-0500-004-1-TS RED | 1430-26-1-0500-005-1-TS BLUE |
| 1430-26-1-0500-006-1-TS BROWN | 1430-26-1-0500-007-1-TS GREEN | 1430-26-1-0500-008-1-TS ORANGE | 1430-26-1-0500-010-1-TS VIOLET | 1430-26-1-0500-011-1-TS GREEN + YELLOW |