



NOTES:

1. METALSHIELDS: STEEL; min. 315µin TIN OVER 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0, BLACK
3. CONTACTS: COPPER ALLOY
PLATING: GOLD FLASH over NICKEL
4. THREADED INSERTS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
5. ADAPTER SCREWD: COPPER ALLOY; NICKEL PLATED
6. ADAPTER HOUSING: PBT GF UL 94 V-0; BLACK
7. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
8. CONNECTOR IS PART MARKED: 163A50079X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale: 2:1 (5:1)	
					material: SEE NOTES	
					title: D-SUB ADAPTER 25pos. MALE / FEMALE with Adapter screws M3	
					dwg no: 16K1A3412	
				part no: 163A50079X		DIN-A3 sh: 1
rev.	description	date	name			
a	Original					
drawn	07.03.14	Henneboel				
appd.	10.03.14	Lehmenkühler				
norm						
d-old						