

MD-219 Series

19-inch display: 5:4 aspect ratio, 1280 x 1024 resolution



- > 19-inch display, 5:4 aspect ratio
- > Sunlight readable 1000-nit LED backlight
- > Color calibrated for ECDIS compliance
- > Full range dimming, 0 to 100%
- > SavvyTouch™ display controls
- > Built-in RS-232/422/485 interfaces
- > Dual power supplies (AC & DC)
- > IP54-rated front panel (IP66 available by request)
- > Optical bonding available on request



Introduction

The MD-219 series of marine displays comes with full range dimming, wide viewing angles, and optional optical bonding. These displays are built with a small-profile modular design that allows easier integration into industrial marine systems, reducing deployment costs and overall time-to-market.



The innovative and user-friendly SavvyTouch display controls offer several unique features not found on any other marine display console: a proximity sensor for convenient adjustments in dark conditions, an info button for immediate updates on power status, and a quick-switch

to adjust between day, dusk, and night-time ECDIS modes (for color-calibrated ECDIS models only).

The MD-219 series displays are compliant with IEC 60945, DNV, ABS, and IACS E10, making them suitable for maritime applications. Their IP54 (IP66-rated model available by request) rated enclosure provides additional protection against dust and moisture above and beyond the limits established by these international standards bodies.


ECDIS-approved models are also available, offering an excellent HMI solution for ECDIS charting and navigation stations.

Appearance



Dimensions

Unit: mm (inch)



Specifications

Display

- Panel Size:** 19" viewable image size
- Panel Type:** MVA
- Aspect Ratio:** 5:4
- Pixels:** 1280 x 1024 (SXGA)
- Response Time:** 20 ms (gray to gray)
- Contrast Ratio:** 2000:1
- Light Intensity:**
 - Standard model: 300 nits
 - High brightness model: 1000 nits
- Viewing Angles:** 178°/178°
- Active Display Area:** 376.32 (H) x 301.06 (V) mm
- Max. No. of Colors:** 16.7M / 8-bit color
- Display Interface:** VGA input x 1, DVI-D input x 1
- Resolution:**
 - VGA: 640 x 480
 - SVGA: 800 x 600
 - XGA: 1024 x 768
 - SXGA: 1280 x 1024

Serial Interface

Serial Standards: 1 RS-232 port (DB9), 1 RS-422/485 port (terminal block)

Optical Isolation Protection: 4 kV

Serial Signals

RS-232: TxD, RxD, DTR, DSR, RTS, CTS, DCD, GND

RS-422: TxD+, TxD-, RxD+, RxD-, GND

RS-485-2w: Data+, Data-, GND

Front Panel

LEDs: MENU, brightness, INFO, ECDIS, Day/Dusk/Night

Smart OSD: Yes

Physical Characteristics

Housing: Aluminum sheet metal

Weight: 7.8 kg

Dimensions: 429 x 387 x 75 mm (16.89 x 15.24 x 2.95 in)

Mounting: VESA, panel, and desktop

Environmental Limits

- Operating Temperature:** -15 to 55°C (5 to 131°F)
- Storage Temperature:** -20 to 60°C (-4 to 140°F)
- Ambient Relative Humidity:** 5 to 95% (non-condensing)

IP Rating:

- Front: IP54 (IP66 available by request)
- Rear: IP22

Anti-Vibration: 0.7 g @ DNV 2.4 (Class A), sine wave, 2-100 Hz, 1 Oct./min., 1.5 hr per axis

Power Requirements

Input Voltage:

- DC: 24 VDC (with tolerance from 18 to 30 VDC, 2-pin terminal block)
- AC: 100 to 240 VAC

Power Consumption: 40 W (max.)

Standards and Certifications

Safety: UL 60950-1, CCC

Hazardous Environments: UL Class 1 Division 2

EMC: EN 55032/24

EMI: CISPR 32, FCC Part 15B Class A

EMS: IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV

IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m

IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV

IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV

IEC 61000-4-6 CS: Signal: 1 kV

IEC 61000-4-8

Marine Standards: IEC-60945 4th, IEC-61174

Marine Type Approval: DNV 2.4 and IACS E10, ABS

Green Product: RoHS, cRoHS, WEEE

Warranty

Warranty Period: 1 year

Details: See www.moxa.com/warranty

We recommend taking the following precautions to minimize heat build-up within the display:

- Position the display within $\pm 40^\circ$ of the vertical.
- Install an external fan to increase airflow upwards through the display if (a) the display is not positioned within $\pm 40^\circ$ of the vertical, (b) the ambient temperature exceeds 25°C , or (c) the display is used in a location with minimal ventilation.

Important Safety Precaution:

Even though the display is rated to operate within the IEC 60945 standard of -15 to 55°C , it is best to ensure that the ambient temperature does not exceed 25°C . Doing so will increase the life of your display and minimize service costs.

Ordering Information

Available Models

MD-219X: 19-inch, 5:4 aspect ratio display (1280x1024), LED backlight, DVI-D/VGA, RS-232 and RS-422/485 serial ports, AC/DC dual power, tape bonding

MD-219Z: 19-inch, 5:4 aspect ratio display (1280x1024), projected capacitive multi-touch, LED backlight, DVI-D/VGA, RS-232 and RS-422/485 serial ports, AC/DC dual power, tape bonding

MD-219Z-HB: 19-inch sunlight readable 1000-nit display, 5:4 aspect ratio (1280x1024), glove-friendly multi-touch, LED backlight, DVI-D/VGA, RS-232 and RS-422/485 serial ports, AC/DC dual power, tape bonding

Optional Accessories (can be purchased separately, for AC power input)

PWC-C13US-3B-183: Power cord with 3-pin connector, USA plug

PWC-C13EU-3B-183: Power cord with 3-pin connector, Euro plug

PWC-C13UK-3B-183: Power cord with 3-pin connector, British plug

PWC-C13AU-3B-183: Power cord with 3-pin connector, Australian plug

PWC-C13CN-3B-183: Power cord with 3-pin connector, Chinese plug

Optional Mounting/Bracket Kits (can be purchased separately)

MPC-MD-2-19-PMTK: 19-inch panel-mounting kit, consisting of 10 mounting clamps

MPC-MD-2-19-VESAMTK: 19-inch VESA-mounting kit (can be used with either 100 x 100 mm or 280 x 150 mm VESA mounts)

MPC-MD-2-19-DMTK w/o hinge: 19-inch desktop mounting kit without hinge

MPC-MD-2-19-DMTK w/ hinge: 19-inch desktop mounting kit with hinge

Package Checklist

- MD-219 display
- VGA cable
- DVI-D cable
- 2-pin terminal block x 1
- 5-pin terminal block x 2
- Documentation and software CD
- Quick installation guide (printed)
- Warranty card