



# Product: <u>83347E</u> ☑

Electronic, 4 C #26 Str SPC, TFE Ins, OA SPC Brd, TFE Tape Jkt, MIL-W-16878/4 (Type E)



# **Product Description**

High Temperature Electronic, 4 Conductor 26AWG (7x34) Silver Plated Copper, TFE Insulation, Overall Silver Plated Copper Braid(85%) Shield, TFE Tape Outer Jacket, MIL-W-16878/4 (Type E)

### **Technical Specifications**

### **Product Overview**

Suitable Applications: M		MIL-W-	MIL-W-16878/4 (Type E) Spec; Extreme High/Low Temperature Environments; up to 600V analog signals & voltage control						
onstructi	on Details								
Conductor									
Element	No. of Elements	Size	Stranding	Material					
Conductor(s)	4	26 AWG	7x34	SC - Silvered Coppe	er				
nsulation									
Element	Materi	al	Nom.	Thickness Nom. In	sulation Diameter	Color Code			
Conductor(s)	PTFE - Polytetraf	luoroethyle	ne 0.010 ir	n (0.25 mm) 0.039 in	(0.99 mm)	White, Black, Red, Green			
Outer Shield									
Shield Type	Material	Cove	rage						
Braid	Silvered Copper (	SC) 85%							
Outer Jacket									
	terial	Nom. Thi	kness I	Nom. Diameter					
PTFE - Polyte	trafluoroethylene	0.011 in (0	.28 mm) 0.	137 in (3.48 mm)					
Overall Cable	Diameter (Nomina	l): 0.137 ir	(3.48 mm)						
		,,	()						
Electrical (	Characteristic	s							
Electricals									
			m. Concoite	ance Cond-to-Cond	Nom Canacitance	e Cond-to-Other (Conds + Shield	) Max. Current		
Element	Nom. Conductor	DCR NO	n. Capacita	ance cond-to-cond	Nom. Capacitance	s oonu-to-other (oonus - onielu			

### Voltage

Voltage Rating 600 V

## **Mechanical Characteristics**

# Temperature UL Temperature Operating 200°C -65°C to +200°C Bend Radius Stationary Min. Installation Min. 1.37 in (34.8 mm) 1.37 in (34.8 mm)

Max. Pull Tension:	14 lbs (6.4 kg)	l
Bulk Cable Weight:	17 lbs/1000ft	

### **Standards and Compliance**

Sustainability:	CA Prop 65
CPR Compliance:	CPR Euroclass: Eca
NEMA Compliance:	NEMA HP3
Military Compliance:	MIL-W-16878/4 (Type E insulated conductors)
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

### **Product Notes**

Notes:	Teflon« is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

### History

Update and Revision: Revision Number: 0.519 Revision Date: 01-20-2023

### **Part Numbers**

### Variants

Item #	Color	Putup Type	Length	UPC	Footnote
83347E 009100	White	Reel	100 ft	612825204329	E
83347E 0091000	White	Reel	1,000 ft	612825204336	E

© 2023 Belden, Inc

### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.