## **Type BLR-412-G** OPTIFUSE **Fuse Block** 12 Pole - Regular, ATC/ATO Auto Blade With 12-Position Grounding Block www.optifuse.com (619) 593-5050 **Specifications: Material:** Max Voltage: 32VDC Housing & Base: PBT, Black Max Current Rating: 30A per Circuit - 100A Max Cover: PC, Clear **Fuse Type:** Regular Auto Blade (APR / ANR series) Terminals: Tinned Copper (Fuses or Circuit Breakers) Button: PA, Red Mounting: 4 mounting holes, 4.5mm diameter **Temperature Rating:** -20° C ~ +85° C Note: Push down Button to open/close Mechanical Dimensions: Inches [mm] 5.47±0.02 [139±0.5] തിതിത ۲ 2.91±0.02 õ 0 ē Ē 3.70+0.02 [74.0±0.5] F [94±0.5] COLORISTER COLORIST $\odot$ $\odot \odot \odot$ Θ 0.177 0.45 0.51 [4.5][11.5] [13.0] 6.46±0.02 Mounting Holes [164±0.5] 2.32±0.02 2.32±0.02 [59±0.5] [59±0.5] 0.55±0.02 [14±0.5] M5 Screws SUS304 M4 Screws x24 SUS304 M5 Screws SUS304

•Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.

-Avoid contact of device with chemical solvent. Prolonged contact may damage the device performance.