

## Termination resistor - FL LCX 50-OHM - 2884978

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



A termination resistor must be screwed on at the end of the leaky wave conductor which does not contain any wireless part. It guarantees an antenna cable termination with the correct impedance and is important for every wireless installation.

### Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	24.8 GRM
Custom tariff number	85176200
Country of origin	China

### Technical data

#### General

Frequency range	2.4 GHz ... 6 GHz
Impedance	50 $\Omega$
Connection method	N (male)

### Classifications

#### eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	19070403
eCl@ss 5.1	19070403
eCl@ss 6.0	19070490
eCl@ss 7.0	19070490
eCl@ss 8.0	19070490

#### ETIM

ETIM 3.0	EC000448
ETIM 4.0	EC000448

## Termination resistor - FL LCX 50-OHM - 2884978

### Classifications

#### ETIM

ETIM 5.0	EC001698
----------	----------

#### UNSPSC

UNSPSC 6.01	20142601
UNSPSC 7.0901	20142601
UNSPSC 11	20142601
UNSPSC 12.01	20142601
UNSPSC 13.2	20142601