

Printed-circuit board connector - PCV 4/10-G-7,62 BK - 1801169

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 20 A, Number of positions: 10, Pitch: 7.62 mm, Color: black, Contact surface: Tin

Key commercial data

| | |
|--------------------------------------|-----------|
| Packing unit | 1 pc |
| Minimum order quantity | 50 pc |
| Weight per Piece (excluding packing) | 22.63 GRM |
| Custom tariff number | 85366990 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|-------------|----------|
| Pitch | 7.62 mm |
| Dimension a | 68.58 mm |

General

| | |
|----------------------------------|------------|
| Range of articles | PCV 4/..-G |
| Rated voltage (III/3) | 400 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I_N | 20 A |
| Color | black |
| Number of positions | 10 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

Printed-circuit board connector - PCV 4/10-G-7,62 BK - 1801169

Classifications

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11 | 39121409 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121409 |

Approvals

Approvals


Approvals


CSA / UL Recognized / cUL Recognized / DNV / GOST / cULus Recognized

Ex Approvals

Approvals submitted

Approval details


| | | |
|---|-------|-------|
| CSA  | | |
| | B | C |
| Nominal current I _N | 20 A | 20 A |
| Nominal voltage U _N | 300 V | 300 V |

| | | |
|---|------|------|
| UL Recognized  | | |
| | B | C |
| Nominal current I _N | 20 A | 20 A |

Printed-circuit board connector - PCV 4/10-G-7,62 BK - 1801169


Approvals

| | B | C |
|--------------------|-------|-------|
| Nominal voltage UN | 300 V | 300 V |

| cUL Recognized  | | |
|--|-------|-------|
| | B | C |
| Nominal current IN | 20 A | 20 A |
| Nominal voltage UN | 300 V | 300 V |

| |
|-----|
| DNV |
|-----|

| |
|--|
| GOST  |
|--|

| |
|--|
| cULus Recognized  |
|--|