



Specifications

Properties

Resin Type Conductive

Surface Resistance

Humidity Independent

Temperature Tolerance

Melting Point

Typical Values

Polypropylene Permanently

 1×10^{2} to < 1×10^{5} ohms per ANSI/ESD STM11.11

Yes

-17° F to +230° F

324° F

Features

- Provides physical protection, with conductive material providing reliable path-to-ground
- · Efficient means of transporting items to the assembly area, and empty totes back to the store room for refilling
- · Extremely durable; includes steel reinforcing frame and rolled over side construction (double thickness)
- · Ships assembled
- Conductive 1 x 10² to < 1 x 10⁵ ohms material provides reliable path-to-ground
- · Superior strength and durability; made from extruded, high impact polypropylene materials
- · Chemical and moisture resistant
- Ideal for use where corrugated and/or paper products cannot be used
- Economical alternative to injection molded products
- Reusable, ensuring best value*
- Made in America

Part Number	Size O.D L x W x D
<u>39140</u>	18" x 12" x 6"
<u>39141</u>	27-1/4" x 12" x 6"
<u>39142</u>	27-1/4" x 18" x 6"



United States of America

If not otherwise noted, tolerance ±10% Specifications and procedures subject to change without notice.

PROTEKTIVE PAK

PLASTEK™ NESTING TOTES

13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578

ProtektivePak.com

DRAWING NUMBER 39140

DATE: June 2017