

6

5

4

3

2

1

F3 MAX-LOC NUT

STAINLESS STEEL SCREWS W/LOCK WASHER (4) REQ'D

STAINLESS STEEL SCREWS W/FLAT WASHER 1<sup>ST</sup> AND O'RING

STAINLESS STEEL SUPPORT RINGS (2) REQ'D

7.41"

MOMENTARY ON/OFF 1NO/1NC (505SW-M) NOT INTERLOCKED

1.18" BETWEEN CENTERS

1.76"

3.52"

2.31"

NOTES:

1. INSTALLATION INSTRUCTIONS, BUTTON ID. LABELS. ARE PACK WITH THE PART.
2. ALL BUTTONS ARE HIGH AMBIENT, CHEMICALLY RESISTANT MATERIAL - COLOR BLACK

RELEASE DRAWING EC NO: WNA2009-0485 DRWN: TVICKERS 2/2/09 CHKD: --- APPR: DTTIUS 2009/02/06 DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE INCHES		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
	▽=0	4 PLACES	mm	INCH	DRAWN BY TV	DATE 2009/02/02	TITLE	
	∇=0	3 PLACES	±----	±----	CHECKED BY HK	DATE 2009/02/02	2 POS PENDANT 5052 W/(505SW-M)	
		2 PLACES	±----	±.010	APPROVED BY DT	DATE 2009/02/02	MOLEX INCORPORATED	
		1 PLACE	±----	±.020	MATERIAL NO. 1301260306	DOCUMENT NO. SD-130126-023	SHEET NO. 1 OF 1	
		ANGULAR ±.5°		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

6

5

4

3

2

1

E

E

D

D

C

C

B

B

A

A