

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



APPLICABLE STANDARD	OPERATING TEMPERATURE RANGE	-35°C T0 +85°C (NOTES 1)	STORAGE TEMPERATURE RANGE	-10°C T0 +60°C
	VOLTAGE	30V AC	APPLICABLE CONNECTOR	BM10*(0.8) -*DP-0.4V (**)
	CURRENT	0.3A		

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	CONFIRMED VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X
ELECTRIC CHARACTERISTICS				
CONTACT RESISTANCE	20mV AC OR LESS 1kHz, 1m A.	100mΩ MAX.	X	-
INSULATION RESISTANCE	100V DC.	50MΩ MIN.	X	-
VOLTAGE PROOF	100V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	-

MECHANICAL CHARACTERISTICS

INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.		X	-																														
<table border="1"> <thead> <tr> <th>PN COUNTS</th> <th>INSERTION FORCE (N MAX)</th> <th>WITHDRAWAL FORCE (N MIN)</th> </tr> </thead> <tbody> <tr><td>BM10*0.8-DS/DP-0.4V</td><td></td><td></td></tr> <tr><td>10</td><td>13.4</td><td>2.6</td></tr> <tr><td>16</td><td>20.7</td><td>2.6</td></tr> <tr><td>20</td><td>27.8</td><td>4.1</td></tr> <tr><td>26</td><td>32.1</td><td>6.2</td></tr> <tr><td>34</td><td>38.6</td><td>6.6</td></tr> <tr><td>40</td><td>41.9</td><td>8.0</td></tr> <tr><td>50</td><td>50.2</td><td>9.8</td></tr> <tr><td>60</td><td>59.5</td><td>11.7</td></tr> </tbody> </table>					PN COUNTS	INSERTION FORCE (N MAX)	WITHDRAWAL FORCE (N MIN)	BM10*0.8-DS/DP-0.4V			10	13.4	2.6	16	20.7	2.6	20	27.8	4.1	26	32.1	6.2	34	38.6	6.6	40	41.9	8.0	50	50.2	9.8	60	59.5	11.7
PN COUNTS	INSERTION FORCE (N MAX)	WITHDRAWAL FORCE (N MIN)																																
BM10*0.8-DS/DP-0.4V																																		
10	13.4	2.6																																
16	20.7	2.6																																
20	27.8	4.1																																
26	32.1	6.2																																
34	38.6	6.6																																
40	41.9	8.0																																
50	50.2	9.8																																
60	59.5	11.7																																
MECHANICAL OPERATION	10TIMES INSERTIONS AND WITHDRAWAL.	① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																														
VIBRATION	FREQUENCY 10 TO 55 TO 10 Hz, APPROX 5min, SINGLE AMPLITUDE 0.75 mm, 100CYCLES, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																														
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																														

ENVIRONMENTAL CHARACTERISTICS				
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → +85 °C TIME 30 → 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHAMBER: WITHIN 2 ~3 MIN)	① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 50MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 100mΩ MAX. ② INSULATION RESISTANCE: 25MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
SULPHUR DIOXIDE	EXPOSED IN 25 PPM FOR 96h, 25°C, 75%. (REFER TO JIS C 60068)	① CONTACT RESISTANCE: 100mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
1	DIS-H-003833	NY, YAMASHIRO	TS, MIYAZAKI	09.04.15
REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT Unless otherwise specified, refer to JIS C 5402 and IEC 60512				
Note	QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-318423-01	

APPROVED	KH, IKEDA	08.04.22
CHECKED	KY, MIDORI, KAWA	08.04.22
DESIGNED	TH, ARAI	08.04.22
DRAWN	SH, HOSODA	08.04.21

HRS	SPECIFICATION SHEET	PART NO.	BM10NB (0.8) -*DS-0.4V (51)
	HIROSE ELECTRIC CO., LTD.	CODE NO.	QL684-****-*--51
			1/1