

box terminal w. control wire voltage tap-off 3 units accessory for: 3VA5 250



| Model | |
|--|---|
| product brand name | SETRON |
| product designation | accessories |
| Accessories | Box terminal |
| General technical data | |
| designation / of the terminal | TS1.4 |
| Connections according IEC | |
| connectable conductor cross-section | |
| <ul style="list-style-type: none"> for copper cable / stranded / minimum for copper cable / stranded / maximum | 25 mm ² 185 mm ² |
| stripped length | 20 mm |
| tightening torque / when using copper cables | |
| <ul style="list-style-type: none"> stranded finely stranded | 25 - 35 mm ² : 6 Nm 50 - 185 mm ² : 12 Nm 35 mm ² : 6 Nm 50 - 150 mm ² : 12 Nm |
| Connections according UL | |
| stripped length | 0.8 in |
| connectable conductor cross-section | |
| <ul style="list-style-type: none"> for copper cable / stranded / minimum for copper cable / stranded / maximum for copper cable / finely stranded / minimum for copper cable / finely stranded / maximum | 4 AWG 350 kcmil 4 AWG 350 kcmil |
| tightening torque / when using copper cables | |
| <ul style="list-style-type: none"> stranded finely stranded | 4 - 1 AWG: 70 lb-in 1/0 - 350 kcmil: 140 lb-in 4 - 1 AWG: 70 lb-in 1/0 - 350 kcmil: 140 lb-in |
| Further information | |

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9233-0JH12>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9233-0JH12>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9233-0JH12

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

7/5/2022

