





④ **USB2.0 COMPLIANT**



NOTES:

1. Material:
 - 1.1 Housing: PBT+30%GF UL94V-0, Color Black
 - 1.2 Shell: SPCC
 - 1.3 Contact :Brass
2. FINISH:
 - 2.1 Contact Area: Selective 5u"Au
 - Solder Area: Tin Plated
 - Under: Ni Plated
3. MECHANICAL:
 - 3.1 Mating Force: 3.57kgf Max.
 - 3.2 Unmating Force: 1.02kgf Min
 - 3.3 Durability: 1500 cycles Min
4. ELECTRICAL:
 - 4.1 Current Rating: 1.5A
 - 4.2 Dielectric Strength: 500V AC FOR 1 MINUTE
 - 4.3 Contact Resistance: 30mΩ Max
 - 4.4 Insulation Resistance: 1000 MΩ Min
- ② 5. Operating temperature: -55°C TO +85°C
- ② 6. Soldering temperature: 245°C±5°C for 3~5 Sec
7. PACKING: Tray

RoHS compliant

| Scale | Free | | | | | | Date | Name | Customer-No. | |
|------------------|-------|-----|-------------------------------|------------|--------|---|------------|--------|-------------------------------|-------|
| TOLERANCE | | ④ | Update | 24.07.2019 | Xavier | Drawn | 07.06.2013 | Winnie | ASSMANN WSW-No. ① AU-Y1008 | |
| .X | ±0.30 | ③ | Change the Pin number | 03.04.2014 | Winnie | Approved | 03.04.2014 | Winnie | | |
| .XX | ±0.20 | ② | Add the soldering temperature | 27.12.2013 | Winnie | | | | | |
| .XXX | ±0.10 | ① | Update the P/N | 10.12.2013 | Winnie | | | | Drawing-No. | |
| DIM | TOL | ① | Update the P/N | 10.12.2013 | Winnie | | | | ASS 5781 CO | rev04 |
| X.° | ±5° | ① | Drawn | 07.06.2013 | Winnie | | | | Replace | SHEET |
| Angle | TOL | ① | Drawn | 07.06.2013 | Winnie | | | | | |
| UNIT | mm | ld. | Modification | Date | Name |  | | | | |

