



Main

Range	Spacial
Accessory / separate part category	Mounting accessory
Product or Component Type	Mounting plate
Device Application	Multi-purpose
Enclosure nominal dimensions	-
Mounting plate description	Telequick perforated
Range compatibility	Spacial SF Spacial SM Spacial SFX Spacial SMX
Device composition	1 mounting plate Fixing elements
Quantity per Set	Set of 1
Material	steel
Surface Finish	Zinc coated

Complementary

Fixing mode	By fixing element - on structure
Height	Fixing centers 22.64 in (575 mm) 23.62 in (600 mm)
Width	Nominal 31.50 in (800 mm) 27.87 in (708 mm)
Cut-out dimensions	11 x 26 mm

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606485133201
Nbr. of units in pkg.	1
Package weight(Lbs)	8.16 lb(US) (3.7 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.10 in (2.8 cm)
Package 1 width	27.95 in (71.0 cm)
Package 1 Length	23.62 in (60.0 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------