



IP67 plastic hoods
IP67 metallized plastic hoods
for rear mount

Identification	No. of contacts	Part number	Drawing	Dimensions in mm
----------------	-----------------	-------------	---------	------------------

Hood ¹⁾ Black thermoplastic	9	09 67 009 043		
	15	09 67 015 043		
	25	09 67 025 043		
	37	09 67 037 043		
	50	09 67 050 043		

Metallized thermo- plastic	9	09 67 009 053		
	15	09 67 015 053		
	25	09 67 025 053		
	37	09 67 037 053		
	50	09 67 050 053		

Please insert digit
for screw option

- Locking screw, thread 4-40 UNC ▶ 8
- Locking screw, thread M3 ▶ 9

Mounting instructions:

- The peeled back cable braiding must not extend over the cable clamp, in order not to damage the gasket or to impair its performance.
- Pull back cable until cable clamp snaps into shielding plate.
- Snap connector into hood.

	a	b	c	d	e	f	g	h	i	Ø	
										min.	max.
9	20	16.5	13.0	20.2	22.1	36.4	25.0	39.8	18.0	6.0	8.0
15	24	16.5	13.0	20.2	26.6	36.4	33.3	48.5	18.0	6.0	10.5
25	24	20.3	13.0	24.0	26.6	43.6	47.0	62.3	45.0	8.0	12.0
37	24	20.3	13.0	24.0	26.6	52.1	63.5	78.6	60.0	8.0	12.0
50	29	22.0	16.0	27.6	32.1	52.1	61.1	75.7	60.0	9.0	14.0

¹⁾ Not to be used with 9 to 50-pole crimp connectors