

Flush-type connector - SACC-E-M8MS-8CON-M10/0,5 - 1424232

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Sensor/actuator flush-type plug, 8-pos., M8, front/screw mounting with M10 fastening thread, with 0.5 m TPE litz wire, 8 x 0.14 mm²



Key commercial data

| | |
|------------------------|---|
| Packing unit | 0 |
| Minimum order quantity | 1 |
| GTIN |  4 046356 712446 |
| Custom tariff number | 85366990 |
| Country of origin | GERMANY |

Technical data

General data

| | |
|---------------------------------|--|
| Rated current at 40°C | 1.5 A |
| Rated voltage | 30 V |
| Number of positions | 8 |
| Volume resistance | ≤ 3 mΩ |
| Insulation resistance | ≥ 100 MΩ |
| Length of cable | 0.5 m |
| Ambient temperature (operation) | -25 °C ... 85 °C (Male connector / female connector) |

General characteristics

| | |
|--------------------------|--------------------------------------|
| Standards/regulations | M8 plug-in connector IEC 61076-2-104 |
| Coding | A - standard |
| Surge voltage category | II |
| Pollution degree | 3 |
| Degree of protection | IP67 |
| Contact material | Cu alloy |
| Contact surface material | Au |
| Contact carrier material | PA 66 |
| Material, knurls | Zinc die-cast, nickel-plated |
| Mounting type | Front mounting M10 |

Flush-type connector - SACC-E-M8MS-8CON-M10/0,5 - 1424232

Technical data

General characteristics

| | |
|-------------------|------------------|
| Connection method | Individual wires |
| Status display | No |

Conductor data

| | |
|---------------------------------|--|
| Cable type | PVC litz wire |
| AWG signal line | 26 |
| Wire colors | white, brown, green, yellow, gray, pink, blue, red |
| Material conductor insulation | PVC |
| Conductor material | Tin-plated Cu litz wires |
| Ambient temperature (operation) | -25 °C ... 85 °C (cable, fixed installation) |

Classifications

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC002061 |
| ETIM 4.0 | EC002635 |
| ETIM 5.0 | EC002635 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 11 | 31251501 |
| UNSPSC 12.01 | 31251501 |
| UNSPSC 13.2 | 31251501 |
| UNSPSC 6.01 | 31251501 |
| UNSPSC 7.0901 | 31251501 |

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250313 |
| eCl@ss 4.1 | 27250313 |
| eCl@ss 5.0 | 27250313 |
| eCl@ss 5.1 | 27143423 |
| eCl@ss 6.0 | 27143423 |
| eCl@ss 7.0 | 27449001 |

Accessories

Accessories

Assembly

Flat nut - SACC-E-MU-M 8 - 1504071




Flat nut with M8 thread


Flush-type connector - SACC-E-M8MS-8CON-M10/0,5 - 1424232

Drawings

Dimensioned drawing



Schematic diagram



M8 plug pin assignment, 8-pos., view of pin side

Mounting panel with feed-through hole