## 84 INCHES LENGTH



Connector A 132114RP SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-316 Continuity/Hi-Pot Connector B 919-386P-51S MCX Plug Straight Brass Gold-Nickel + Heatshrink

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

		Connector A	A Cable			Connector B		
	nrt #:	132114RP		Part #:	RG-316	Part #:	919-386P-51S	
Des	escription:	SMA PLUG RP R	G316 50O	Description:	RG-316 - ST 0.102	Description:	MCX PLUG RG174 RG188 RG316 500	
Тур	pe:	SMA		Dielectric:	ST	Туре:	MCX	
Ger	ender:	Plug		Shielding:	Braid	Gender:	Plug	
Boo	ody Type:	Straight		Diameter:	0.102	Body Type:	Straight	
Cor	ontact Type:	Crimp		Impedance:50 OhmSheathing:None	50 Ohm	Contact Type:	Crimp	
Pol	olarity:	Reverse			None	Polarity:	Standard	
Imp	pedance:	50 Ohm		Testing:	Continuity Hi-Pot Impedance: 50 Ohm		50 Ohm	Jhm
Mo	ounting:	Cable		Length:	84 Inches	Mounting:	Cable	
Boo	ody Material:	Brass				Body Material:	Brass	
Boo	dy Finish:	Gold				Body Finish:	Gold-Nickel	
IP F	Rating:	None				IP Rating:	None	
Cor	ontact Material:	Beryllium Copper				Contact Material:	Brass	
Cor	ontact Finish:	Gold				Contact Finish:	Gold	
Max	ax. Freq.:	12.4 GHz				Max. Freq.:	6 GHz	
	Booting: SMA Plug Straigh		t RP			Booting:	MCX Plug Straight	
	J	5 5				Clocking:	0°	
Amphenol PROPRIETARY INFO FOR ANY PURPOSE INC. IT MAY NOT B			PROPRIETARY INFORMATION A FOR ANY PURPOSE DETRIMENT INC. IT MAY NOT BE REPRODUC	VING MAY CONTAIN PATENTED OR ARY INFORMATION AND MUST NOT BE USED URPOSE DETRIMENTAL TO CUSTOM CABLE Y NOT BE REPRODUCED OR TRANSCRIBED		Title: SMA-ST-PL-RP/MCX-ST-PL G316 84I		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY:
CONTROLLED DOCUMENT - DO NOT COPY			IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.		NG Part No:			



## **RoHS 2015/863 Compliance Statement**

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/1/2023

Part Number: Q-6801F0005084I

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-PL-RP/MCX-ST-PL G316 84I

This information is valid as of the date indicated for the item (part number) listed.

**Director of Quality Assurance** 

Janice Frank