



基板取付穴推奨寸法
RECOMMENDED P.C.BOARD HOLE DIM.

注記
NOTE

△ 全極数が偶数の場合にのみ適用。
TO BE APPLIED ONLY WHEN ALL CKTS. ARE EVEN.

34.88	31.68	09-75-2094	5274-09A	9
26.96	23.76	↑ -2074	↑ -07A	7
23	19.8	↑ -2064	↑ -06A	6
19.04	15.84	↑ -2054	↑ -05A	5
15.08	11.88	↑ -2044	↑ -04A	4
11.12	7.92	↓ -2034	↓ -03A	3
7.16	3.96	09-75-2024	5274-02A	2
B	A	オーダー番号 (EDP NO.) ORDER NO. (EDP NO.)	ENG. NO.	極数 CKTS

REVISED EC NO: J2009-2884 DRWN: YSHIBATA 2009/06/24 CHKD: THARUYAMA 2010/03/15 APPR: NUKITA 2010/03/15	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 4:1		DESIGN UNITS METRIC		THIRD ANGLE PROJECTION		
		10 UNDER	±0.2	DRAWN BY H. HIRAMATO		DATE 1991/05/13		TITLE KK 3.96 WAFER ASS'Y RIGHT ANGLE WITH LOCK				
		10 OVER 30 UNDER	±0.25	CHECKED BY M. FUKUSHIMA		DATE 1991/05/15		MOLEX INCORPORATED				
		30 OVER	±0.3	APPROVED BY M. ENOMOTO		DATE 1991/05/15						
REV	DESCRIPTION	ANGULAR ±3 °		MATERIAL NO.		DOCUMENT NO.		SHEET NO.		SEE TABLE		
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		SD-5274-001		1 OF 1		