

## Universal Reversible USB 2.0 Cable (Right / Left-Angle Reversible A to B M/M), 3 ft. (0.91 m)

MODEL NUMBER: UR022-003-RA



Reversible Right / Left Angle USB "A" connector plugs in any direction

### Description

The UR022-003-RA USB 2.0 Right / Left Angle "A" to B device cable with Universal / Reversible "A" connector meets or exceeds USB 2.0 specifications. Backward compatible with older USB 1.1 applications as well. USB 2.0 cabling includes superior foil shielding for reliable, error-free data communications. The data transfer rates of USB 2.0 (up to 480 Mbps) make them perfect for multimedia applications. Features nickel-plated connectors and gold-plated copper contacts for superior conductivity. The cable is manufactured with molded connectors and integral strain relief for extra durability and long life.

### Features

- 3-ft. (0.91 m), USB 2.0 Right / Left Angle A-Male to B-Male, with Universal / Reversible "A" connector
- USB 2.0 compliant, to 480Mbps transfer rates
- Backward compatible with previous USB generations
- Gold plated contacts and molded ends provide a lifetime of use
- 28AWG Data Pair, 24AWG Power pair

## Specifications

| OVERVIEW           |                      |
|--------------------|----------------------|
| UPC Code           | 037332179463         |
| Technology         | USB 2.0 (High Speed) |
| Cable Type         | Passive              |
| PHYSICAL           |                      |
| Cable Jacket Color | Black                |

### Highlights

- 3-ft. (0.91 m), USB 2.0, Right / Left Angle A to B Peripheral device cable
- Universal, Reversible "A" connector allows plugging in any direction

### System Requirements

- Any USB device requiring a USB cable
- USB2.0 performance only when used with USB2.0 device and USB2.0 controller

### Package Includes

- Universal Reversible USB 2.0 Right / Left Angle A-Male to B-Male Device Cable - 3-ft. (0.91 m)

|                                     |                              |
|-------------------------------------|------------------------------|
| Cable Length (ft.)                  | 3                            |
| Cable Length (m)                    | 0.91                         |
| Shipping Dimensions (hwd / in.)     | 0.25 x 5.00 x 7.00           |
| Shipping Dimensions (hwd / cm)      | 0.64 x 12.70 x 17.78         |
| Shipping Weight (lbs.)              | 0.10                         |
| Shipping Weight (kg)                | 0.05                         |
| <b>ENVIRONMENTAL</b>                |                              |
| Operating Temperature Range         | 14° to 122°F (-10° to 50°C)  |
| Storage Temperature Range           | 5° to 140°F (-15° to 60°C)   |
| Operating Humidity Range            | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range              | 0% to 90% RH, Non-Condensing |
| <b>CONNECTIONS</b>                  |                              |
| Side A - Connector 1                | REVERSIBLE USB A (MALE)      |
| Side B - Connector 1                | USB B (MALE)                 |
| Connector Style                     | Angled                       |
| <b>STANDARDS &amp; COMPLIANCE</b>   |                              |
| Product Compliance                  | RoHS                         |
| <b>WARRANTY &amp; SUPPORT</b>       |                              |
| Product Warranty Period (Worldwide) | Lifetime limited warranty    |