



# 2379-2401 MHz Cavity Band Pass Filter



**ANATECH ELECTRONICS INC**  
RF & Microwave Filters & Products

**Part Number: AE2390B11666**

## Electrical Specifications

**Center Frequency:** 2390 MHz  
**Bandwidth:** 22 MHz  
**Insertion Loss:** 1.5dB Max.  
**Return Loss:** 14dB Min.  
**Rejection:** ≥50dB @ F0±20MHz  
**Impedance:** 50 Ohms  
**Power Handling:** 50 Watts


## Mechanical

**Mounting Method:** 4-40 Threaded holes  
**Connector Type:** SMA(F)  
**Dimensions:** 4.7 X 2.5 x 1.42 in.

## Environmental

**Operating Temperature:** -40°C to +70°C  
**Storage Temperature:** -55°C to +85°C  
**Shock:** 20 G. 11ms  
**Vibration:** 20 G. 5 to 200Hz

## Outline Drawing:



Tolerance: +/-0.01 inches [ +/- 0.3mm]

Angles: +/- 1 Deg.

\*Tolerance as shown unless otherwise specified in the datasheet electrical specification tables above.

\*When max dimensions are called out the above tolerances do not apply as long as it is under the max call out.

**70 Outwater Lane Phone: (973) 772-4242**  
**Garfield, NJ 07026 Fax : (973) 321-3941**

**Email: [sales@anatechelectronics.com](mailto:sales@anatechelectronics.com)**  
**Web: [www.anatechelectronics.com](http://www.anatechelectronics.com)**