

USB Electrical Outlet, ATUR Series, Ultra High Speed USB Charger Outlets, Integrated 20A Duplex Tamper Resistant Receptacle with Wall Plate

The **ATUR Series** of USB charger outlets can charge up to two USB devices simultaneously while at the same time giving you AC access to the 2 electrical outlets. With the option of either a 3.4A or 5A power charging rating, you can be assured to quickly charge a wide range of electronic devices. The UL Listed **ATUR Series** of 20 Amp USB electrical outlets feature a child safe tamper resistant duplex that complies with 2011 NEC Article 406.14. The smart charging technology of the **ATUR Series** includes over-current, over charging, and short circuit protection and precisely reads the power need of your two devices to deliver optimal power accordingly without overcharging.



The **ATUR Series** of AC wall outlet with USB charging ports is shipped with a wall plate to ensure a professional, safe installation. This high tech fast charge USB power outlet is compatible with USB 1.1/2.0/3.0 devices. Since the **ATUR** 2 port USB wall charger is UL Listed it is ideal also for commercial usage, including airports, hotels, restaurants, schools, offices and hospitals.

Installation of the **ATUR** USB duplex receptacle is made easy with the ability to back or side wire for broad compatibility with diverse wiring needs. The **ATUR** 2 port USB wall charger can fit in any standard in-wall outlet box. It is also compatible with standard wall-plates.

Safety is another important feature of the **ATUR Series** of USB charger wall outlets as validated by the compliance with UL498 requirements. The tamper resistant AC outlet with USB charging ports features an internal shutter mechanism to prevent children from sticking objects into the outlet.

The ATUR Series of 2 port USB wall chargers is compatible with a wide range of electronic devices including, but not limited to:

• iPad®

- Tablets

- Digital Cameras

• iPad®Mini

- Windows Phones

- MacBook

Tablets

- Kindle®

- Chromebook

iPhones®iPod®

Galaxy Tab™
 Bluetooth Headsets

- Other USB Products

Model Number	Charging Capacity	Description
ATUR3.4-20-W	2.5A, 0.9A	White USB Duplex Receptacle, TR, 20A, Charge Capacity 3.4 Amps with Wall Plate
ATUR3.4-20-I	2.5A, 0.9A	Ivory USB Duplex Receptacle, TR, 20A, Charge Capacity 3.4 Amps with Wall Plate
ATUR3.4-20-B	2.5A, 0.9A	Black USB Duplex Receptacle, TR, 20A, Charge Capacity 3.4 Amps with Wall Plate
ATUR5.0-20-W	5A	White USB Duplex Receptacle, TR, 20A, Charge Capacity 5 Amps with Wall Plate
ATUR5.0-20-I	5A	Ivory USB Duplex Receptacle, TR, 20A, Charge Capacity 5 Amps with Wall Plate
ATUR5.0-20-B	5A	Black USB Duplex Receptacle, TR, 20A, Charge Capacity 5 Amps with Wall Plate

3 and 10 Multi-Packs Now Available Online!

Specifications:

 Voltage:
 125 Vac

 Current:
 20A

 Wire Size:
 14-10 AWG

 USB Voltage:
 5 Vdc

 USB Current:
 3.4A

Dimensions (H x W x D): $104 \times 43.4 \times 44 \text{ mm}$ Operating Temperature Range: -20°C to $+60^{\circ}\text{C}$



