Data sheet 3716.8 ZQI 2,5/8 YE





Insulated cross-connector, No. of poles: 8, Mounting type: Plug in, Width: 39.7 mm, Rated cross-section: 2.5 mm², Colour: Yellow

RAL: 1026

Business data

Buomood data	
Article number	<u>3716.8</u>
Article name	ZQI 2,5/8 YE
GTIN (EAN)	4044211060343
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	4.58 g
Weight per piece (including packaging)	4.7 g
Unit of weight	G
Customs number	85389099
Country of origin	CZ
Prio-Article	3716.8
Product description	Insulated cross-connector





Dimensions Length 4.5 mm Width 39.7 mm Pitch size 5 mm Ratings Voltage with partition, max. 800 V Voltage without partition, max. 800 V Rated current 24 A Rated cross-section 2.5 mm² Contamination degree 3 Connection data No. of poles 8 Materials Material Copper alloy Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available V Touch protection is available V Number of bridged terminals 8 Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No		
Length 4.5 mm Width 39.7 mm Pitch size 5 mm Ratings Voltage with partition, max. 800 V Voltage without partition, max. 800 V Rated current 24 A Rated coross-section 2.5 mm² Contamination degree 3 Connection data Seconsection No. of poles 8 Materials Copper alloy Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Mounting type Plug in Insulation available V Touch protection is available V Number of bridged terminals 8 Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Technical data	
Width 39.7 mm Pitch size 5 mm Ratings 800 V Voltage with partition, max. 800 V Rated current 24 A Rated cross-section 2.5 mm² Contamination degree 3 Connection data 8 No. of poles 8 Materials Copper alloy Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Insulation available V Touch protection is available V Number of bridged terminals 8 Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Dimensions	
Pitch size	Length	4.5 mm
Ratings Voltage with partition, max. 800 V Voltage without partition, max. 800 V Rated current 24 A Rated cross-section 2.5 mm² Contamination degree 3 Connection data No. of poles 8 Materials Materials Material Copper alloy Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 8 Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Width	39.7 mm
Voltage with partition, max. 800 V Voltage without partition, max. 800 V Rated current 24 A Rated cross-section 2.5 mm² Contamination degree 3 Connection data 8 No. of poles 8 Materials Copper alloy Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Mounting type Plug in Insulation available √ Touch protection is available √ Number of bridged terminals 8 Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Pitch size	5 mm
Voltage without partition, max. Rated current Rated cross-section 2.5 mm² Contamination degree 3 Connection data No. of poles 8 Materials Materials Material Copper alloy Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available V Touch protection is available V Number of bridged terminals 8 Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note	Ratings	
Rated current 24 A Rated cross-section 2.5 mm² Contamination degree 3 Connection data 8 No. of poles 8 Materials Copper alloy Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Insulation available V Touch protection is available V Number of bridged terminals 8 Environmental Product Compliance Yes REACH Candidate Substance Note No	Voltage with partition, max.	800 V
Rated cross-section 2.5 mm² Contamination degree 3 Connection data 8 No. of poles 8 Materials Copper alloy Material Copper alloy Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available V V Touch protection is available V Number of bridged terminals 8 Environmental Product Compliance Yes REACH Candidate Substance Note No	Voltage without partition, max.	800 V
Contamination degree 3 Connection data No. of poles 8 Materials Material Copper alloy Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 Working temperature, min40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available Touch protection is available Number of bridged terminals 8 Environmental Product Compliance REACH Candidate Substance Note No	Rated current	24 A
Connection data No. of poles Materials Materials Material Material Copper alloy Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available V Touch protection is available V Number of bridged terminals 8 Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note	Rated cross-section	2.5 mm²
Materials Material Copper alloy Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 Working temperature, min40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available Touch protection is available Number of bridged terminals 8 Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note Surface Tin-plated Copper alloy Surface Tin-plated Polyamide 6.6 Furit-plated Polyamide 6.6 Plug in 40 °C V-2 V-2 Working temperature, max. 105 °C Further technical data Suprational Su	Contamination degree	3
Materials Material Copper alloy Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available Touch protection is available V Number of bridged terminals 8 Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Connection data	
Material Copper alloy Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 Working temperature, min40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 8 Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	No. of poles	8
Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 Working temperature, min40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available Touch protection is available Number of bridged terminals Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note Tin-plated Touch encodes Tin-plated Touch of C Polyamide 6.6 V-2 Hug in V Substance Note Touch protection is available V No	Materials	
Flammability class UL 94 Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available V Touch protection is available Number of bridged terminals Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note Polyamide 6.6 V-2 V-2 V-2 V-2 V-2 V-2 V-2 V-	Material	Copper alloy
Flammability class UL 94 Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available V Touch protection is available Number of bridged terminals Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Surface	Tin-plated
Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available V Touch protection is available Number of bridged terminals Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Insulation housing	Polyamide 6.6
Working temperature, max. Further technical data Mounting type Plug in Insulation available Touch protection is available Number of bridged terminals Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Flammability class UL 94	V-2
Further technical data Mounting type Plug in Insulation available Touch protection is available Number of bridged terminals 8 Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Working temperature, min.	-40 °C
Mounting type Plug in Insulation available ✓ Touch protection is available ✓ Number of bridged terminals 8 Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Working temperature, max.	105 °C
Insulation available Touch protection is available Number of bridged terminals Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Further technical data	
Touch protection is available Number of bridged terminals Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Mounting type	Plug in
Number of bridged terminals 8 Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Insulation available	✓
Environmental Product Compliance REACH Conform Yes REACH Candidate Substance Note No	Touch protection is available	✓
REACH Conform Yes REACH Candidate Substance Note No	Number of bridged terminals	8
REACH Candidate Substance Note No	Environmental Product Compliance	
	REACH Conform	Yes
RoHS Conform Yes	REACH Candidate Substance Note	No
100	RoHS Conform	Yes

Data sheet 3716.8 ZQI 2,5/8 YE



Media



Accessories

##INVERSE##CONTA-CONNECT



Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3568.2	ZRKD 2,5/LED1(RD)/24V DC BG	4044211059125	100 ST



Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3569.2	ZRKD 2,5/LED2(RD)/24V DC BG	4044211059132	100 ST



Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3572.2	ZRKD 2,5/D3 BG	4044211059163	100



Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3573.2</u>	ZRKD 2,5/D4 BG	4044211059170	100



Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3574.2</u>	ZRKD 2,5/D5 BG	4044211059187	100 ST





Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour:Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3645.2	ZRKD 2,5/LED(RD)/230V AC BG	4044211146733	100 ST



Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3570.2	ZRKD 2,5/D1 BG	4044211059149	100



Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3571.2	ZRKD 2,5/D2 BG	4044211059156	100



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17481.2	ZST 2,5/1/1A/Q BG	4044211205201	50 ST



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 66.3 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17493.2	ZST 2,5/13/1A/Q BG	4044211205324	10 ST



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 71.4 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17494.2	ZST 2,5/14/1A/Q BG	4044211205331	10 ST

3716.8 ZQI 2,5/8 YE



##INVERSE##CONTA-CONNECT



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3653.2	ZRKS 2,5/2A/2S BG	4044211177683	100



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3652.2	ZRKS 2,5/2A/1S BG	4044211177676	100



Feed-through terminal, Plug-in connection, Mounting type: Mounting rail TS 35/7.5, Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3655.2	ZRKS 2,5/2S BG	4044211177706	100



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 25.5 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17485.2	ZST 2,5/5/1A/Q BG	4044211205249	50 ST



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 56.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17491.2	ZST 2,5/11/1A/Q BG	4044211205300	10 ST



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 76.5 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17495.2	ZST 2,5/15/1A/Q BG	4044211205348	10 ST



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 816 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17496.2	ZST 2,5/16/1A/Q BG	4044211205355	10 ST





Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3650.2	ZRKS 2,5/1A/1S BG	4044211177652	100



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3651.2	ZRKS 2,5/1A/2S BG	4044211177669	100



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 45.9 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17489.2	ZST 2,5/9/1A/Q BG	4044211205287	25 ST



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 51 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17490.2	ZST 2,5/10/1A/Q BG	4044211205294	25 ST



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3673.2</u>	ZST 2,5/1A/Q/Z BG	4044211177843	100



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 20.4 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17484.2	ZST 2,5/4/1A/Q BG	4044211205232	50 ST



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 35.7 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17487.2	ZST 2,5/7/1A/Q BG	4044211205263	25 ST





Feed-through terminal, Plug-in connection, Mounting type: Mounting rail TS 35/7.5, Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3654.2	ZRKS 2,5/4S BG	4044211177690	100



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 10.2 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17482.2	ZST 2,5/2/1A/Q BG	4044211205218	50 ST



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 15.3 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17483.2	ZST 2,5/3/1A/Q BG	4044211205225	50 ST



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 40.8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17488.2	ZST 2,5/8/1A/Q BG	4044211205270	25 ST



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 61.2 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17492.2	ZST 2,5/12/1A/Q BG	4044211205317	10 ST



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3672.2</u>	ZST 2,5/1A/Q BG	4044211177836	100



Feed-through terminal, Tension-spring connection, Mounting type: Plug in, Rated cross-section: 2.5 mm², Width: 30.6 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17486.2	ZST 2,5/6/1A/Q BG	4044211205256	25 ST





Ex feed-through terminal for direct mount, ATEX-certified, Tension-spring connection, Mounting type: Mounting surface, Rated cross-section: 25 mm², Width: 51 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1729.2	ZSRK 2,5/2A-D Ex BG	4044211129699	100 ST



Feed-through terminal for direct mount, Tension-spring connection, Mounting type: Mounting surface, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3588.2	ZSRK 2,5/2A-D BG	4044211151966	100



Feed-through terminal for direct mount, Tension-spring connection, Mounting type: Mounting surface, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Black-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
3638.2	ZSLN 2,5/2A-D BKYE	4044211080570	100 ST



Feed-through terminal for direct mount, Tension-spring connection, Mounting type: Mounting surface, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Black-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
3639.2	ZSLN 2,5/2A-RC BKYE	4044211080556	100 ST



Feed-through terminal for direct mount, Tension-spring connection, Mounting type: Mounting surface, Rated cross-section: 2.5 mm², Width: 11.1 mm, Colour: Black-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
3640.2	ZSLN 2,5/2A-D/F BKYE	4044211080563	50 ST



Feed-through terminal for direct mount, Tension-spring connection, Mounting type: Mounting surface, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3587.2	ZSRK 2,5/2A-RC BG	4044211151942	100





Feed-through terminal for direct mount, Tension-spring connection, Mounting type: Mounting surface, Rated cross-section: 2.5 mm², Width: 11.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3595.2	ZSRK 2,5/2A/D/F BG	4044211059545	50



Fuse-disconnect terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3616.2	ZTRK 2,5/2A/ZS BG	4044211059804	100



Fuse-disconnect terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3621.2	ZTRK 2,5/3A/ZS BG	4044211059859	100



Fuse-disconnect terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3626.2</u>	ZTRK 2,5/4A/ZS BG	4044211059903	100



Disconnect-blade terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3605.2	ZTRK 2,5/4A/MT BG	4044211059699	100



Basic terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3611.2</u>	ZTRK 2,5/4A/OT BG	4044211059750	100





Three-level initiator terminal | Multi-wire terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour:Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3590.2	ZIKD 2,5 BG	4044211059460	50



Three-level initiator terminal | Multi-wire terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3592.2	ZIKD 2,5/PE/L/L BG	4044211059507	50



Three-level initiator terminal | Multi-wire terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3594.2	ZIKD 2,5/PE/L/N BG	4044211059538	50 ST



Disconnect-blade terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3603.2	ZTRK 2,5/2A/MT BG	4044211059675	100



Disconnect-blade terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3604.2</u>	ZTRK 2,5/3A/MT BG	4044211059682	100



Basic terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3609.2	ZTRK 2,5/2A/OT BG	4044211059736	100





Basic terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3610.2	ZTRK 2,5/3A/OT BG	4044211059743	100



Three-level initiator terminal | Multi-wire terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17037.2	ZIKD 2,5/L-L-N BG	4044211155742	50 ST



Double-level terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3564.2	ZRKD 2,5/N/DU	4044211059088	100 ST



Double-level terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3566.2	ZRKD 2,5/N/PE	4044211059101	100 ST



Double-level terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3575.2</u>	ZRKD 2,5/ZBA BG	4044211059194	100



Three-level initiator terminal | Multi-wire terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3591.2</u>	ZIKD 2,5/SV BG	4044211059484	50





Ex double-level terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1707.2	ZRKD 2,5 Ex BG	4044211110949	100



Double-level terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3562.2	ZRKD 2,5 BG	4044211151836	100



Double-level terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3563.2	ZRKD 2,5/SV BG	4044211059064	100



Double-level terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3565.2	ZRKD 2,5/DU/PE	4044211059095	100 ST



Double-level terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3576.2	ZRKD 2,5/SV/ZBA BG	4044211059217	100



Double-level terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3577.2	ZRKD 2,5/N/DU/ZBA	4044211059231	100 ST



Double-level terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3578.2	ZRKD 2,5/DU/PE/ZBA	4044211059248	100 ST





Double-level terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3579.2	ZRKD 2,5/N/PE/ZBA	4044211059255	100 ST



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1704.2	ZRK 2,5/2A Ex BG	4044211058401	100



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3501.2	ZRK 2,5/3A BG	4044211151690	100



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1169.2	ZSRK 2,5/2A/SAS BG	4044211128647	100



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1700.2	ZSRK 2,5/2A/15 Ex BG	4044211059354	100



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1702.2	ZSRK 2,5/2A Ex BG	4044211059316	100



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1705.2	ZRK 2,5/3A Ex BG	4044211110925	100





Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3500.2	ZRK 2,5/2A BG	4044211151683	100



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3583.2</u>	ZSRK 2,5/2A BG	4044211151874	100



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3585.2	ZSRK 2,5/2A/15 BG	4044211151904	100



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1703.2	ZSRK 2,5/3A Ex BG	4044211059620	100



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1706.2	ZRK 2,5/4A Ex BG	4044211058463	100



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3599.2	ZSRK 2,5/3A/15 BG	4044211152024	100



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 15/5.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1701.2	ZSRK 2,5/3A/15 Ex BG	4044211059590	100

3716.8 ZQI 2,5/8 YE



##INVERSE##CONTA-CONNECT



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3502.2	ZRK 2,5/4A BG	4044211151713	100



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3600.2	ZSRK 2,5/3A BG	4044211152031	100

##INVERSE##CONTA-CONNECT



Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3569.2	ZRKD 2,5/LED2(RD)/24V DC BG	4044211059132	100 ST

##INVERSE##CONTA-CONNECT



Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3568.2	ZRKD 2,5/LED1(RD)/24V DC BG	4044211059125	100 ST

3716.8 ZQI 2,5/8 YE



##INVERSE##CONTA-CONNECT

Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour:Beige

I	Article number	Article name	GTIN (EAN)	Packaging unit
	3570.2	ZRKD 2,5/D1 BG	4044211059149	100

##INVERSE##CONTA-CONNECT



Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3571.2	ZRKD 2,5/D2 BG	4044211059156	100

##INVERSE##CONTA-CONNECT



Double-level terminal with electronic components, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

7.3	Article number	Article name	GTIN (EAN)	Packaging unit
	<u>3572.2</u>	ZRKD 2,5/D3 BG	4044211059163	100