

ZBRV1

Harmony XB5R, Visual feedback for ZBRT transmitters for wireless and batteryless push button



Main

Range of Product	Harmony XB5R
Product or Component Type	Visual feedback
Device short name	XB5R
Light source colour	White
Product compatibility	ZBRRA - receiver V2.2 and above) ZBRRC - receiver V2.2 and above) ZBRRD - receiver V2.2 and above) ZBRA1 - antenna V3.3 and above) ZBRN1 - wireless access point V3.32 and above) ZBRN2 - wireless access point V3.32 and above)
Sale per indivisible quantity	1

Complementary

[Us] rated supply voltage	3 V with battery
Signalling type	Blinking
Light source	Protected LED
Bulb base	Integral LED
Light block supply	Direct
Embedding Depth	1.65 in (42 mm)
CAD overall height	1.47 in (37.4 mm)
CAD overall width	0.95 in (24.2 mm)
CAD overall depth	1.56 in (39.6 mm)
Net Weight	0.02 lb(US) (0.009 kg)
Standards	EN/IEC 60947-1 EN/IEC 60947-5-1

Environment

Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Relative humidity	95 % 32...131 °F (0...55 °C) without condensation
Mechanical durability	50000 cycles
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27
Vibration resistance	5 gn 11...500 Hz)IEC 60068-2-6 +/- 10 mm 2...11 Hz)IEC 60068-2-6
Electromagnetic compatibility	Electrostatic discharge immunity test 8 kV in free air (in insulating parts)) IEC 61000-4-2 Electrostatic discharge immunity test 4 kV on contact (on metal parts)) IEC 61000-4-2 Susceptibility to electromagnetic fields 10 V/m 80...1000 MHz) IEC 61000-4-3 Susceptibility to electromagnetic fields 3 V/m IEC 61000-4-3 Susceptibility to electromagnetic fields 3 V/m 1000...6000 MHz) IEC 61000-4-3
Product Certifications	CSA UL Listed EAC

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.







Ordering and shipping details

Category	22470 - XB5R WIRELESS PUSH BUTTON
Discount Schedule	I
GTIN	3606482035065
Nbr. of units in pkg.	1
Package weight(Lbs)	0.60 oz (17 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.30 in (3.3 cm)
Package 1 width	1.69 in (4.3 cm)
Package 1 Length	2.05 in (5.2 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	75
Package 2 Weight	3.20 lb(US) (1.452 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.