

Technical Data Sheet Rev 05.221130

6 port Managed USB 2.0 Hub w/ 15KV ESD Surge Protection

Model Number: CG-6PU2MGD



Features

- Compliant with USB Specification 2.0
- Supports 480Mbps (High speed), 12Mbps (Full-speed) and 1.5Mbps (Low-speed) Speed
- Software Manageable Bus power for each Port
- Supports 15KV ESD Level 4 Protection for Each Port
- Supports +7~48V DC Wide Range Input Power

Package Contents

- 2-Pin Terminal Block
- DIN rail bracket
- Hub
- Screw Lock USB Cable
- Screw Pack

Specifications

OVERVIEW

Model No	CG-6PU2MGD
Product Type	USB Hub
Compliance	REACH RoHS TAA
UPC	045079163089
Country of Origin	Taiwan
LED indicators	Power
Chipset	GL852GT
Electrical Protections	15kv

PHYSICAL

Ship Weight (lbs)	1.09 lbs
Ship Weight (kg)	0.49 kg
Item Weight	0.6 lbs
Length	5.2 inches
Width	1.43 inches
Height	2.42 inches
Material	Steel
Color	Black
Mountable	Din-Rail Surface Mount Wall Mount

Specifications Cont.

CONNECTIONS

USB Specification	USB 2.0
Maximum Data Rate	480 Mbps
Downstream Port Count	6
Downstream Port Type	6x Type A USB 2.0
Works as Standalone Charger	N - Requires Host to function
Can be Bus Powered	Y - Supports Bus Power
Bus Power Isolation Supports Disabling Bus Power	N

Power

Input Voltage	7 ~ 48V DC
Power Connector	Phoenix 2-pin
Idle Power Draw	40mA @ 12 VDC
Max Power Draw	17.5W
Max Per Port Draw	1.5A (7.5W)

ENVIRONMENTAL

Operating Temperature	0C ~ 60C
Storage Temperature	-20C ~ 75C
Operating Humidity	5% to 95% RH

OS SUPPORT

Supported Operating Systems	Linux Windows 10 Windows 8 Windows 7
-----------------------------	--

WARRANTY

Warranty Period	1 Year
-----------------	--------

PRODUCT URL

CG-6PU2MGD Product Page	https://www.coolgear.com/product/6-port-managed-usb-2-0-hub-w-15kv-esd-surge-protection
-------------------------	---