



Main

| | |
|-------------------------------|----------------------------------|
| Range of Product | Harmony Electromechanical Relays |
| Product or Component Type | Socket |
| Contact terminal arrangement | Mixed |
| Product compatibility | Plug-in relay RPM 2 C/O |
| Shape of pin | Flat |
| Device short name | RPZ |
| Sale per indivisible quantity | 10 |

Complementary

| | |
|--|--|
| [I _{th}] conventional free air thermal current | 16 A |
| [U _e] rated operational voltage | < 250 V |
| Tightening torque | < 1 N.m M3.5 |
| Fixing mode | By screw panel) Clip-on 35 mm symmetrical DIN rail) |
| Marking | CE |
| Width | 1.18 in (30 mm) |
| Net Weight | 0.12 lb(US) (0.054 kg) |

Environment

| | |
|---------------------------------------|---|
| Connections - terminals | - screw clamp terminals, flexible with cable end 1 x 0.5...1 x 2.5 mm ² / AWG 20...AWG 14 - screw clamp terminals, solid without cable end 1 x 0.5...1 x 1.5 mm ² / AWG 20...AWG 16 - screw clamp terminals, flexible with cable end 2 x 0.5...2 x 2.5 mm ² / AWG 20...AWG 14 - screw clamps terminals, solid without cable end 2 x 0.5...2 x 1.5 mm ² / AWG 20...AWG 16 |
| Standards | IEC 61984 |
| Product Certifications | UL CSA |
| Ambient Air Temperature for Storage | -40...185 °F (-40...85 °C) |
| Ambient air temperature for operation | -40...131 °F (-40...55 °C) |
| IP degree of protection | IP20 conforming to EN/IEC 60529 |
| Dielectric strength | 2500 V |

Ordering and shipping details

| | |
|-----------------------|--|
| Category | 21128 - ZELIO ICE CUBE RELAY ACCESSORIES |
| Discount Schedule | CP2 |
| GTIN | 3389119402293 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 2.05 oz (58 g) |
| Returnability | Yes |
| Country of origin | TW |

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.18 in (3 cm) |
| Package 1 width | 1.18 in (3 cm) |
| Package 1 Length | 0.59 in (1.5 cm) |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Weight | 22.22 oz (630 g) |
| Package 2 Height | 2.36 in (6 cm) |
| Package 2 width | 4.41 in (11.2 cm) |
| Package 2 Length | 5.91 in (15 cm) |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 200 |
| Package 3 Weight | 27.31 lb(US) (12.388 kg) |
| Package 3 Height | 11.81 in (30 cm) |
| Package 3 width | 11.81 in (30 cm) |
| Package 3 Length | 15.75 in (40 cm) |


Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty


| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions



- (1) Relays
- (2) Protection module
- (3) Maintaining clamp

Wiring Diagram



Symbols shown in blue correspond to Nema marking.