



- NOTES:
1. MATERIAL: UNFILLED NYLON, UL94V-2, COLOR: NATURAL
 2. FINISH: N/A
 3. THIS PART CONFORMS TO PS-08-50.
 4. PACKAGING SPECIFICATION: PK-6422-001
 5. CONNECTOR TO BE USED WITH CRIMP TERMINAL SERIES 2878, 2478, 2578
 6. RIB WIDTH .040 / 1.02 REF. EXCEPT WHEN RIB IS ADJACENT TO THE HOOK. THEN RIB WIDTH IS .025 ±.006 / 0.64 ±.015
 7. DIMENSIONS GIVEN ACROSS CENTERLINES ARE SYMMETRICAL ABOUT THOSE CENTERLINES WITHIN ONE HALF THE TOTAL TOLERANCE.
 8. FOR THIS PART WITHOUT HOOK, SEE 2574 SERIES.
 9. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.

NO. OF CKT'S	DIM. C	DIM. B	DIM. D
3	.632 (16.05)	.312±.002 (7.92±.05)	.618 (15.70)
4	.788 (20.02)	.468±.002 (11.89±.05)	.774 (19.66)
5	.944 (23.98)	.624±.003 (15.85±.08)	.922 (23.42)
6	1.100 (27.94)	.780±.003 (19.81±.08)	1.078 (27.38)
7	1.256 (31.90)	.936±.003 (23.77±.08)	1.232 (31.29)
8	1.412 (35.86)	1.092±.004 (27.74±.10)	1.388 (35.26)
9	1.568 (39.83)	1.248±.004 (31.70±.10)	1.544 (39.22)
10	1.724 (43.79)	1.404±.006 (35.66±.15)	1.700 (43.18)
11	1.880 (47.75)	1.560±.006 (39.62±.15)	1.854 (47.09)
12	2.036 (51.71)	1.716±.006 (43.59±.15)	2.010 (51.05)
13	2.192 (55.68)	1.872±.006 (47.55±.15)	2.164 (54.97)
14	2.348 (59.64)	2.028±.007 (51.51±.18)	2.318 (58.88)
15	2.504 (63.60)	2.184±.007 (55.47±.18)	2.474 (62.84)
16	2.660 (67.56)	2.340±.007 (59.44±.18)	2.631 (66.83)
17	2.816 (71.53)	2.496±.008 (63.40±.20)	2.784 (70.71)
18	2.972 (75.49)	2.652±.009 (67.36±.23)	2.954 (75.03)
19	3.128 (79.45)	2.808±.009 (71.32±.23)	3.095 (78.61)
20	3.284 (83.41)	2.964±.009 (75.29±.23)	3.251 (82.58)
21	3.440 (87.38)	3.120±.010 (79.25±.25)	3.407 (86.54)
22	3.596 (91.34)	3.276±.011 (83.21±.25)	3.562 (90.47)
23	3.752 (95.30)	3.432±.011 (87.17±.28)	3.716 (94.39)
24	3.908 (99.26)	3.588±.012 (91.14±.30)	3.871 (98.32)

ADD NOTES EC NO. UCF2012-3660 DRAWN/KIPPER 2012/05/10 CHKD/BANDERSON 2012/05/10 APPR/FSMTH 2012/05/22	QUALITY SYMBOLS ▽=0 ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) <table border="1"> <tr><th></th><th>mm</th><th>INCH</th></tr> <tr><td>4 PLACES</td><td>±.010</td><td>±.010</td></tr> <tr><td>3 PLACES</td><td>±.025</td><td>±.014</td></tr> <tr><td>2 PLACES</td><td>±.036</td><td>±.014</td></tr> <tr><td>1 PLACE</td><td>±.050</td><td>±.014</td></tr> <tr><td>0 PLACE</td><td>±.075</td><td>±.014</td></tr> </table>			mm	INCH	4 PLACES	±.010	±.010	3 PLACES	±.025	±.014	2 PLACES	±.036	±.014	1 PLACE	±.050	±.014	0 PLACE	±.075	±.014	DIMENSION STYLE IN/MM	SCALE 4:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
			mm	INCH																					
4 PLACES	±.010	±.010																							
3 PLACES	±.025	±.014																							
2 PLACES	±.036	±.014																							
1 PLACE	±.050	±.014																							
0 PLACE	±.075	±.014																							
DRAWN BY DATE SAMIEC PEREZ 1994/06/09 CHECKED BY DATE PATEL 1994/06/09 APPROVED BY DATE	MATERIAL NO. SEE CHART		DOCUMENT NO. SD-6422		SHEET NO. 1 OF 2																				

EDGE CARD CONNECTOR
 .156/(3.96) CL CRIMP
 2574 WITH HOOK
molex
 INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

