

August 1991

Features


- 45A, 50V and 60V
- $r_{DS(on)} = 0.040\Omega$
- SOA is Power-Dissipation Limited
- Nanosecond Switching Speeds
- Linear Transfer Characteristics
- High Input Impedance
- Majority Carrier Device
- High-Current, Low-Inductance Package

Description

The RFH45N05 and RFH45N06 are n-channel enhancement-mode silicon-gate power field-effect transistors designed for applications such as switching regulators, switching converters, motor drivers, relay drivers, and drivers for high-power bipolar switching transistors requiring high speed and low gate-drive power. These types can be operated directly from integrated circuits.


The RFH-types are supplied in the JEDEC TO-218AC plastic package.

Package



Terminal Diagram

N-CHANNEL ENHANCEMENT MODE



Absolute Maximum Ratings ($T_C = +25^\circ\text{C}$), Unless Otherwise Specified

	RFH45N05	RFH45N06	UNITS	
Drain-Source Voltage	V_{DS}	50	60	V
Drain-Gate Voltage ($R_{GS} = 1M\Omega$)	V_{DGR}	50	60	V
Continuous Drain Current	I_D	45	45	A
Pulsed Drain Current	I_{DM}	100	100	A
Gate-Source Voltage	V_{GS}	± 20	± 20	V
Maximum Power Dissipation				
$T_C = +25^\circ\text{C}$	P_D	150	150	W
Linear Derating Factor		1.2	1.2	W/ $^\circ\text{C}$
Operating and Storage Temperature	T_J, T_{STG}	-55 to +150	-55 to +150	$^\circ\text{C}$

Specifications RFH45N05, RFH45N06

ELECTRICAL CHARACTERISTICS, at Case Temperature (T_c) = 25°C unless otherwise specified.

CHARACTERISTIC	SYMBOL	TEST CONDITIONS	LIMITS				UNITS
			RFH45N05		RFH45N06		
			Min.	Max.	Min.	Max.	
Drain-Source Breakdown Voltage	BV_{DSS}	$I_D = 1 \text{ mA}$ $V_{GS} = 0$	50	—	60	—	V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{GS} = V_{DS}$ $I_D = 1 \text{ mA}$	2	4	2	4	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 40 \text{ V}$ $V_{DS} = 50 \text{ V}$	—	1	—	—	μA
		$T_c = 125^\circ\text{C}$ $V_{DS} = 40 \text{ V}$ $V_{DS} = 50 \text{ V}$	—	50	—	50	
			—	—	—	—	
Gate-Source Leakage Current	I_{GSS}	$V_{GS} = \pm 20 \text{ V}$ $V_{DS} = 0$	—	100	—	100	nA
Drain-Source On Voltage	$V_{DS(on)}^{\#}$	$I_D = 22.5 \text{ A}$ $V_{GS} = 10 \text{ V}$	—	0.9	—	0.9	V
		$I_D = 45 \text{ A}$ $V_{GS} = 10 \text{ V}$	—	3.6	—	3.6	
Static Drain-Source On Resistance	$r_{DS(on)}^{\#}$	$I_D = 22.5 \text{ A}$ $V_{GS} = 10 \text{ V}$	—	.04	—	.04	Ω
Forward Transconductance	$g_{fs}^{\#}$	$V_{DS} = 10 \text{ V}$ $I_D = 22.5 \text{ A}$	10	—	10	—	mho
Input Capacitance	C_{iss}	$V_{DS} = 25 \text{ V}$	—	3000	—	3000	pF
Output Capacitance	C_{oss}	$V_{GS} = 0 \text{ V}$	—	1800	—	1800	
Reverse Transfer Capacitance	C_{rss}	$f = 1\text{MHz}$	—	750	—	750	
Turn-On Delay Time	$t_d(on)$	$V_{DS} = 30 \text{ V}$	40(typ)	80	40(typ)	80	ns
Rise Time	t_r	$I_D = 22.5 \text{ A}$	310(typ)	475	310(typ)	475	
Turn-Off Delay Time	$t_d(off)$	$R_{\theta en} = R_{\theta gs} = 50\Omega$	220(typ)	350	220(typ)	350	
Fall Time	t_f	$V_{GS} = 10 \text{ V}$	240(typ)	375	240(typ)	375	
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	RFH45N05, RFH45N06 Series	—	0.83	—	0.83	$^\circ\text{C/W}$

$\#$ Pulsed: Pulse duration = 300 μs max., duty cycle = 2%.

SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS

CHARACTERISTIC	SYMBOL	TEST CONDITIONS	LIMITS				UNITS
			RFH45N05		RFH45N06		
			Min.	Max.	Min.	Max.	
Diode Forward Voltage	V_{SD}^*	$I_{SD} = 22.5\text{A}$	—	1.4	—	1.4	V
Reverse Recovery Time	t_{rr}	$I_F = 4\text{A}$, $d_f/d_r = 100 \text{ A}/\mu\text{s}$	150 (typ.)		150 (typ.)		ns

* Pulse Test: Width $\leq 300 \mu\text{s}$, Duty cycle $\leq 2\%$.

4
N-CHANNEL
POWER MOSFETS

RFH45N05, RFH45N06




Fig. 1 - Maximum safe operating areas for all types.




Fig. 2 - Power vs. temperature derating curve for all types.




Fig. 3 - Typical normalized gate threshold voltage as a function of junction temperature for all types.




Fig. 4 - Normalized drain-to-source on resistance to junction temperature for all types.




Fig. 5 - Typical transfer characteristics for all types.

RFH45N05, RFH45N06




Fig. 6 - Normalized switching waveforms for constant gate-current. Refer to Harris application notes AN-7254 and AN-7260




Fig. 7 - Typical saturation characteristics for all types.




Fig. 8 - Typical drain-to-source on resistance as a function of drain current for all types.




Fig. 9 - Capacitance as a function of drain-to-source voltage for all types.




Fig. 10 - Typical forward transconductance as a function of drain current for all types.




Fig. 11 - Switching Time Test Circuit.

4
N-CHANNEL
POWER MOSFETS