

Dynamic Series | Dynamic 4000 Series

TE Internal #: 1-1903329-3 Housing, Receptacle, Wire-to-Board, 6 Position, .25 in [6.35 mm] Centerline, Crimp, 2 Row, Black, Mating Retention, Wire & Cable, Dynamic 4000 Series

View on TE.com >

Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings >

Receptacle and Tab Housing: 6.35 mm pitch, 600V



Connector Product Type: Housing Connector & Housing Type: Receptacle Connector System: Wire-to-Board Number of Positions: 6 Centerline (Pitch): 6.35 mm [.25 in]

All Receptacle and Tab Housing: 6.35 mm pitch, 600V (27)

Features

Product Type Features



Connector Product Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	6
Number of Rows	2
Body Features	
Primary Product Color	Black
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Mating Retention	With
Connector Mounting Type	Cable Mount (Free-Hanging)

1-1903329-3

Housing, Receptacle, Wire-to-Board, 6 Position, .25 in [6.35 mm] Centerline, Crimp, 2 Row, Black, Mating Retention, Wire & Cable, Dynamic 4000 Series



Housing Features	
Centerline (Pitch)	6.35 mm[.25 in]
Dimensions	
Row-to-Row Spacing	8.8 mm[.346 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power
Product Compliance For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235)

Halogen Content

Does not contain REACH SVHC

Not Low Halogen - contains Br or Cl > 900 ppm.

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

1-1903329-3

Housing, Receptacle, Wire-to-Board, 6 Position, .25 in [6.35 mm] Centerline, Crimp, 2 Row, Black, Mating Retention, Wire & Cable, Dynamic 4000 Series






TE Part # CAT-D9934-A78A Receptacle and Tab Housing: 6.35 mm pitch, 600V

Also in the Series | Dynamic 4000 Series





Wire-to-Board Connector Contacts(17)

Customers Also Bought





1-1903329-3

Housing, Receptacle, Wire-to-Board, 6 Position, .25 in [6.35 mm] Centerline, Crimp, 2 Row, Black, Mating Retention, Wire & Cable, Dynamic 4000 Series



Documents

Product Drawings DYNAMIC 4200M REC HSG 6P XX

English

CAD Files

Customer View Model ENG_CVM_CVM_1-1903329-3_H.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1903329-3_H.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1903329-3_H.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 1-1773721-5_DYNAMIC_SERIES_QRG

English

1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH

Japanese

1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Agency Approvals TUV Certificate

English