


ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A	B	C	D	E	F	G	H	I	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING
	MIN IN (mm)	MAX IN (mm)	IN (mm) +/- .030 (.762mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .030 (.762mm)	IN (mm) +/- .020 (.508mm)		
AL-07-50-MH-IT-30	.062 (1.587mm)	1.750 (44.450mm)	8.000 (203.200mm)	.052 (1.320mm)	.177 (4.495mm)	.364 (9.245mm)	.183 (4.468mm)	.208 (5.283mm)	.361 (9.169mm)	.325 (8.255mm)	.049 (1.244mm)	50 (222)	HB
AL-14-120-MH-IT-30	.187 (4.762mm)	4.062 (103.174mm)	15.750 (400.050mm)	.075 (1.905mm)	.298 (7.569mm)	.513 (13.030mm)	.298 (7.569mm)	.256 (6.502mm)	.510 (12.954mm)	.345 (8.763mm)	.074 (1.879mm)	120 (534)	HB
 ACT ADVANCED CABLE TIES, INC.													
ADVANCED CABLE TIES – HIGH TEMP, UV & IMPACT RESISTANT MOUNTING HEAD SERIES CABLE TIES													
COLOR DESIGNATIONS: IT-30 = HIGH TEMP, IMPACT RESISTANT, UV BLACK HEAT STABILIZED									MATERIAL: NYLON 6/6 POLYAMIDE				
B	4/298/17	JA	KT	KT	NEW LOGO ADDED.		SHEET 1 OF 1		REV.: B		DRAWING NO.: IMPACT-MH-B		
A	4/2/15	JA	KT	KT	INITIAL RELEASE		DRAWN BY		DATE		CHECK	SCALE	
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA		4/28/17		KT	NONE	

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.61.1