


# 10GBase-T Magnetics Modules

Designed to Support 10GBase-T  
Transceivers



- Compliant with IEEE 802.3 standard
- Qualified with top 10Gig PHY Manufacturer
- RoHS peak reflow temperature rating: 245°C
- Low profile package for PCI Express
- Fine-tune magnetics to specific PHY vendors

## Electrical Specifications @ 25°C - Operating Temperature 0°C to 70°C

RoHS Compliant Part Number	Channel Option	Insertion Loss (dB or better)		Return Loss (dB or better)		Common to Differential Mode Rejection (dB or better)		Crosstalk (dB or better)		Hipot (Vrms MIN)	MSL
		100 kHz	1-500 MHz	1-40 MHz	40-500 MHz	1-250 MHz	250-500 MHz	1-100 MHz	100-500 MHz		
H7019NL	4	-3.0	-1.0 (-0.6 dB TYP)	-18	-17+ 10* LOG (f/40)	-30	-22	-40	-30	1500	1
H7028NL	4	-3.0	-1.0 (-0.6 dB TYP)	-18	-17+ 10* LOG (f/40)	-30	-22	-40	-30	1500	1
H7029NL	4	-3.0	-1.0 (-0.6 dB TYP)	-18	-17+ 10* LOG (f/40)	-30	-22	-40	-30	1500	1
HX7028NL <sup>1</sup>	4	-3.0	-1.0 (-0.6 dB TYP)	-18	-17+ 10* LOG (f/40)	-30	-22	-40	-30	1500	1
H7800NL	4	-3.0	-1.0 (-0.6 dB TYP)	-18	-17+ 10* LOG (f/40)	-30	-22	-40	-30	1500	1
H7037NL	5	-3.0	-1.0 (-0.6 dB TYP)	-23	-23+ 10* LOG (f/40)	-40	-25	-40	-25	1500	1
H7137NL	5	-3.0	-1.0 (-0.6 dB TYP)	-23	-23+ 10* LOG (f/40)	-40	-25	-40	-25	1500	1


### Notes:

1. Extended Operating temperature (-40°C to +85°C)

Note: When ordering Tape & Reel packaging, add a "T" suffix at the end of the part number, e.g. H7137NLT.

## Mechanical

### H7019NL, H7028NL, H7029NL, HX7028NL



Weight .....1.2 grams  
Tube .....35

Dimensions:  $\frac{\text{Inches}}{\text{mm}}$  Unless otherwise specified, all tolerances are  $\pm \frac{.010}{.025}$

USA 858 674 8100

Germany 49 7032 7806 0

Singapore 65 6287 8998

Shanghai 86 21 62787060

China 86 755 33966678

Taiwan 886 3 4356768


# 10GBase-T Magnetics Modules

Designed to Support 10GBase-T  
Transceivers



## Mechanicals


### H7800NL



Weight .....1.0 grams  
 Tape & Reel .....700  
 Tube .....20

Dimensions:  $\frac{\text{Inches}}{\text{mm}}$  Unless otherwise specified, all tolerances are  $\pm \frac{.010}{0,25}$

### H7037NL, H7137NL



Dimensions:  $\frac{\text{Inches}}{\text{mm}}$  Unless otherwise specified, all tolerances are  $\pm \frac{.010}{0,25}$



# 10GBase-T Magnetics Modules

Designed to Support 10GBase-T  
Transceivers

## Schematics

H7019NL, H7028NL, H7029NL, HX7028NL

H7037NL, H7137NL



## For More Information

**Pulse Worldwide  
Headquarters**  
12220 World Trade Drive  
San Diego, CA  
92128  
U.S.A.

Tel: 858 674 8100

**Pulse Europe**  
Einsteinstrasse 1  
D-71083 Herren-  
berg  
Germany

Tel: 49 7032 7806

**Pulse China Headquarters**  
B402, Shenzhen Academy of  
Aerospace Technol-  
ogy Bldg.  
10th Kejinan Road  
High-Tech Zone  
Nanshan District  
Shenzen, PR China  
518057

**Pulse North China**  
Room 2704/2705  
Super Ocean Finance  
Ctr.  
2067 Yan An Road  
West  
Shanghai 200336  
China

**Pulse South Asia**  
135 Joo Seng Road  
#03-02  
PM Industrial Bldg.  
Singapore 368363

Tel: 65 6287 8998  
Fax: 65 6287 8998

**Pulse North Asia**  
3F, No. 198  
Zhongyuan Road  
Zhongli City  
Taoyuan County 320  
Taiwan R. O. C.  
Tel: 886 3 4356768  
Fax: 886 3 4356823  
(Pulse)

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2012. Pulse Electronics, Inc. All rights reserved.