# 5-2149521-1 V ACTIVE

#### STRADA


TE Internal #: 5-2149521-1

PCB Mount Receptacle, Vertical, Board-to-Board, 6 Position, 9.14 mm [.36 in] Centerline, Gold, Through Hole - Press-Fit, Power &

Signal, Black

View on TE.com >

Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: PCB Mount Receptacle

PCB Mount Orientation: Vertical Connector System: Board-to-Board

Number of Positions: 6 Number of Rows: 3

### **Features**

## **Product Type Features**

PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Pairs per Column	0
Number of Power Positions	6
Number of Pairs	0
Stackable	No
Number of Signal Positions	0
PCB Mount Orientation	Vertical
Number of Positions	6
Number of Rows	3
Board-to-Board Configuration	Parallel
Electrical Characteristics	
Dielectric Withstanding Voltage (Max)	750 VAC
Insulation Resistance	1000 ΜΩ

100 Ω

Impedance



Operating Voltage	6 VDC
Signal Characteristics	
Data Rate	16 Gb/s
Body Features	
Primary Product Color	Black
Contact Features	
PCB Contact Termination Area Plating Material Thickness	.5 – 2.54 μm[19.68 – 100 μin]
Contact Layout	Staggered
Mating Tab Width	4.5 mm[.177 in]
Mating Tab Thickness	.3 mm[.011 in]
PCB Contact Termination Area Plating Material Finish	Matte
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.076 μm[3 μin]
Contact Type	Socket
Contact Current Rating (Max)	18 A
Termination Features	
Rectangular Termination Post & Tail Thickness	.2 mm[.008 in]
Rectangular Termination Post & Tail Width	.74 mm[.029 in]
Termination Post & Tail Length	2.05 mm[.08 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Mechanical Attachment	
PCB Mount Alignment Type	Post Polarization
Mating Retention	With
Mating Alignment	With
PCB Mount Retention	With
PCB Mount Alignment	With
Connector Mounting Type	Board Mount
Housing Features	
Mating Entry Location	Тор
Centerline (Pitch)	9.14 mm[.36 in]



Housing Material	LCP (High Temp Thermoplastic)
Dimensions	
Connector Height	4.49 mm[.176 in]
PCB Thickness (Recommended)	.06 mm[.8 in]
Usage Conditions	
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	48
Packaging Type	Tray

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on



requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



N,25





## Customers Also Bought



TE Part #1410189-3 MULTIGIG RT T2 7RW H-LFT,ET2



TE Part #1410186-1 MULTIGIG RT T2 .8" BP H-LFT



TE Part #1410142-1 MULTIGIG RT T2 .8" BP FULL RGH









### **Documents**

#### **CAD Files**

Customer View Model

ENG\_CVM\_CVM\_5-2149521-1\_A.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5-2149521-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-2149521-1\_A.3d\_stp.zip

English

PCB Mount Receptacle, Vertical, Board-to-Board, 6 Position, 9.14 mm [.36 in] Centerline, Gold, Through Hole - Press-Fit, Power & Signal, Black



By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

**Application Specification** 

English

Product Environmental Compliance

TE Material Declaration

English