



- 注;  
 1. 適用ターミナルは 61116, 61118  
 2. 嵌合するブラクハウジングは 170394

1	170895	-9	黒	10
1		-8	灰	9
1		-7	紫	8
1		-6	青	7
1		-5	緑	6
1		-4	黄	5
1		-3	橙	4
1		-2	赤	3
1		-1	茶	2
	170895	-1	自然色	1

F1	REVISED PER ECR-17-011147	JB	DZ	08JUN 2018
F	ECN NO. 232491	REVISED	BY DZ	08JUN 2018
E2	ADDED (REV. 01)	BY DZ	08JUN 2018	
E1	REVISED (REV. 01)	BY DZ	08JUN 2018	
E	REVISED (REV. 01)	BY DZ	08JUN 2018	
D	ADDED	BY DZ	08JUN 2018	
C	REVISED (REV. 01)	BY DZ	08JUN 2018	
B	ADDED CIRCUIT NO. X.S.	BY DZ	08JUN 2018	
A	REDRAWN	BY DZ	08JUN 2018	

C-170895		品番 NUMBER	名称 NAME	備注 REMARKS	ITEM NO.
C-170895		170895	15極	メイトンロックチャップハウジング	1
EQUIPMENT REQUIRED PER ASSEMBLY		1500BY AMP Japan, Inc. ALL RIGHTS RESERVED. AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING		参考図面 (CUSTOMER COPY) (REFERENCE ONLY)	
MATERIAL		EQUIPMENT WIRE RANGE		TE Connectivity	
66ナイロン		AMP SWG		CLASS	
FINISH		INSULATION DIA.		TYPE	
3; 表参照		TOLERANCE		SCALE	
DR. K. Shiroi 11/17/20		EXCEPT AS NOTED		LOC. SIZE	
CHK. K. Shiroi 11/17/20		2-1		REV. C-170895	
DE. K. Shiroi 11/17/20		35 NAME		REV. F1	
EQUIPMENT REQUIRED PER ASSEMBLY		DESCRIPTION		DESCRIPTION	

DIMENSIONS IN MM. TO 0.01 SCALE PRINT