



1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.
- MATERIAL:  
 HOUSING & COVER - THERMOPLASTIC, BLACK.  
 TERMINALS - PHOS BRONZE PLATED WITH EITHER .000050 MINIMUM GOLD PLATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE. .000050 MIN TOTAL ON MATING SURFACE. GOLD FLASH PLATED ON TERMINATING SIDE. .000050 MINIMUM NICKEL UNDERPLATE OVER ENTIRE TERMINAL.
3. COVER SHOWN LOOSE BUT SHIPPED ASSEMBLED.
4. WIRE RANGE: 26 AWG SOLID THRU 30 AWG SOLID AND 28 AWG STRANDED RIBBON CABLE.
5. ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.
6. FLAT CABLE SHALL BE FURNISHED BY CUSTOMER.
7. MATING FACE CONSISTS OF TWO ROWS OF TERMINALS ON .085 CENTERS, TERMINATING SIDE CONSISTS OF TERMINALS ON .100 CENTERS FOR AN EFFECTIVE .050 TERMINATION.
8. PANEL THICKNESS RANGE:  
 FRONT PANEL MOUNTING - .125 MAX  
 REAR PANEL MOUNTING - .062 MAX
9. FOR MORE INFORMATION REFER TO AMP PRODUCT SPECIFICATION 108-6076 & APPLICATION SPEC 114-6030.

.620	.310	.149	1.575	REAR PANEL MOUNTING
.640	.320	.126	1.488	FRONT PANEL MOUNTING
DIM D	DIM C	DIM B	DIM A	DESCRIPTION

THIS DRAWING IS A CONTROLLED DOCUMENT

DATE	REV	DESCRIPTION
GP	00	
J		REVISED FOR ISO-9001:2015

REVISIONS

DATE	REV	DESCRIPTION
17APR08	BMI	W/M

AS SHOWN 554103-1  
 DESCRIPTION PART NUMBER

YPO Electronics Corporation  
 Henderson, NV 89105-5088

PLUG ASSEMBLY, 24 POSITION  
 PANEL MOUNTING, LDM PROFILE,  
 CHAMP LATCH

APPLICATION SPEC  
 A2100779-554103

CUSTOMER DRAWING

SCALE 2:1 SHEET 1 OF 1 REV J