

TE Internal #: 151680 Rectangular Power Connectors, Housing, Cap, Wire-to-Wire, 2 Position, 7.11 mm [.279 in] Centerline, Wire & Cable, UL 94V-2 View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: Housing

Connector & Housing Type: Cap

Connector System: Wire-to-Wire

Number of Positions: 2

Centerline (Pitch): 7.11 mm [.279 in]

Features

Product Type Features

Rectangular Power Connector Type	Housing
Connector & Housing Type	Сар
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	2
Number of Power Positions	2
Number of Signal Positions	2
Number of Rows	1
Electrical Characteristics	
Operating Voltage	250 VDC
Contact Features	
Contact Current Rating (Max)	15 A
Contact Retention Within Housing	With

Rectangular Power Connectors, Housing, Cap, Wire-to-Wire, 2 Position, 7.11 mm [. 279 in] Centerline, Wire & Cable, UL 94V-2



Contact Type	Socket
Termination Features	
Termination Method to Wire & Cable	Crimp
Housing Features	
Centerline (Pitch)	7.11 mm[.279 in]
Housing Color	Natural
Housing Material	Nylon
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
UL Flammability Rating	UL 94V-2
Glow Wire Rating	Standard Part - Not Glow Wire
Packaging Features	
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent

Rectangular Power Connectors, Housing, Cap, Wire-to-Wire, 2 Position, 7.11 mm [. 279 in] Centerline, Wire & Cable, UL 94V-2



chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Customers Also Bought



Rectangular Power Connectors, Housing, Cap, Wire-to-Wire, 2 Position, 7.11 mm [. 279 in] Centerline, Wire & Cable, UL 94V-2







Documents

Product Drawings 2 WAY MATE-N-LOK SOC HSG NAT.

English

CAD Files 3D PDF

3D

Customer View Model ENG_CVM_CVM_151680_Y.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_151680_Y.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_151680_Y.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English

Product Environmental Compliance Product Compliance English

Product Compliance

English

Rectangular Power Connectors, Housing, Cap, Wire-to-Wire, 2 Position, 7.11 mm [. 279 in] Centerline, Wire & Cable, UL 94V-2

