12.54 [0.494]

3.88 [0.153]

ANODE O

 $1.50 \ [0.059]$ 

ANDDE

15.00 [0.591]

10.00 [0.394]

2.00 [0.079]

- Ø3,00 [Ø0,118]

- 1.00 [0.040]

1.00 [0.039]

→ CATHODE

## SSL-LX100T123UWC

## PRELIMINARY IN P/N DIR

## ELECTRO-OPTICAL CHARACTERISTICS TA=25°C


| PARAMETER                    | SYMBOL     | MIN            | TYP | MAX            | UNITS   | TEST COND             |
|------------------------------|------------|----------------|-----|----------------|---------|-----------------------|
| PEAK WAVELENGTH              |            |                | -   |                | nm      |                       |
| FORWARD VOLTAGE              | Vf         |                | 3.5 | 4.0            | V       | $I_f = 350 \text{mA}$ |
| REVERSE VOLTAGE              | $V_r$      | 5              |     |                | V       | I <sub>r</sub> = 10µA |
| AXIAL INTENSITY(*1)          | Ιv         | 27             | 37  |                | lm      | $I_f = 350MA$         |
| CHROMATICITY COORDINATES(*2) | X<br>Y     | 0.245<br>0.225 |     | 0.361<br>0.385 |         | $I_f = 350 \text{mA}$ |
| VIEWING ANGLE                |            |                | 25  |                | 2x thet | .a                    |
| EMITTED COLOR:               | WHITE      |                |     |                |         |                       |
| EPOXY LENS FINISH: \         | WATER CLEA | ۸R             |     |                |         |                       |

## LIMITS OF SAFE OPERATION AT 25°C

| MAX          | UNITS                                   |
|--------------|---|
|              | OINITS                                  |
| 500          | mA                                      |
| 350          | mA                                      |
| 1.4          | W                                       |
| -1.2         | mW/ <b>'</b> C                          |
| -40  TO  +85 | *C                                      |
| 260          | <b>°</b> C                              |
| 3            | SEC                                     |
|              | 350<br>1.4<br>-1.2<br>-40 T0 +85<br>260 |

<sup>\*</sup>T<10µS

CAUTION: STATIC SENSITIVE DEVICE FOLLOW PROPER E.S.D. HANDLING PROCEDURES



WHEN WORKING WITH THIS PART.



UNCONTROLLED DOCUME \*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN= +D.0.00 +D.0.000 +D.0.000

REV. PART NUMBER SSL-LX100T123UWC

Ø10.00mm 1 WATT THROUGH HOLE, HIGH POWER LED. InGaN WHITE LED, WATER CLEAR LENS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

CHECKED BY: DRAWN BY:

APPROVED BY: DATE: 12.19.07

PAGE: 1 OF 1 SCALE: N/A

<sup>\*1.</sup> AXIAL INTENSITY TESTING CONDITION: 550nm WAVELENGTH.

<sup>\*2.</sup> THE ICI STANDARD COLORIMETRIC SYSTEM.