

# T1 SPE IP20 1x2xAWG22/7 PUR 3,0m



| Part number        | 33 28 020 2002 030                     |
|--------------------|--|
| Specification      | T1 SPE IP20 1x2xAWG22/7 PUR 3,0m       |
| HARTING eCatalogue | https://b2b.harting.com/33280202002030 |

Image is for illustration purposes only. Please refer to product description.

#### Identification

| System cabling<br>IARTING T1 Industrial<br>Cable assemblies |
|---|
|   |
| Cable assemblies  |
|   |
| Pre-assembled on both sides                                 |
| IARTING T1 Industrial<br>Overmoulded                        |
| IARTING T1 Industrial<br>Overmoulded                        |
| Copper cable (round)  |
| lalogen-free<br>Dil resistant<br>lame retardant             |
|   |
|   |

| Cable length    | 3 m            |
|-----------------|----------------|
| Number of cores | 2              |
| Core structure  | 1x 2x AWG 22/7 |

### **Technical characteristics**

| Rated current                | 4 A               |
|------------------------------|-------------------|
| Rated voltage                | 60 V DC           |
| Transmission characteristics | 600 MHz Bandwidth |
| Data rate                    | 10 Mbit/s         |
|                              | 100 Mbit/s        |
|                              | 1 Gbit/s          |

Page 1 / 3 | Creation date 2023-06-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com



#### Technical characteristics

| Contact resistance                     | ≤20 mΩ   |
|--|--|
| Shielding resistance                   | ≤100 mΩ  |
| Limiting temperature                   | -40 +80 °C unmoved<br>-25 +80 °C moved             |
| Mating cycles                          | ≥1,000   |
| Degree of protection acc. to IEC 60529 | IP20   |
| Test voltage U <sub>DC</sub>           | 1 kV (contact-contact)<br>2.25 kV (contact-ground) |

#### Material properties

| Material (cable)                     | PUR (polyurethane)  |
|--------------------------------------|---|
| Colour (cable)                       | Yellow  |
| RoHS                                 | compliant   |
| ELV status                           | compliant   |
| China RoHS                           | e   |
| REACH Annex XVII substances          | Not contained   |
| REACH ANNEX XIV substances           | Not contained   |
| REACH SVHC substances                | Yes   |
| REACH SVHC substances                | Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate |
| ECHA SCIP number                     | 69a540f5-7b39-4e74-832e-14618bec5629                      |
| California Proposition 65 substances | Yes   |
| California Proposition 65 substances | Nickel  |

## Specifications and approvals

|                | IEC 63171-6   |
|----------------|---|
|                | IEEE 802.3bu (remote power supply over PoDL = Power over Data Line) |
|                | IEEE 802.3cg (10BASE-T1)  |
| Specifications | IEEE 802.3bw (100BASE-T1)   |
|                | IEEE 802.3bp (1000BASE-T1)  |
|                | IEC 60332-1-2 Flame retardancy                                      |
|                | EN 60811-404 Oil resistance   |

### Commercial data

| Packaging size                 | 1        |
|--------------------------------|----------|
| Net weight                     | 130 g    |
| Country of origin              | Latvia   |
| European customs tariff number | 85444290 |

Page 2 / 3 | Creation date 2023-06-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com



#### Commercial data

GTIN

eCl@ss

5713140246997

27060390 Ready-made data cable (unspecified)

Page 3 / 3 | Creation date 2023-06-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com