



| | | | | | | | | | | | | | | | | | | | | |
|------|------|----|-----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|-------|----|------|
| PIN | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 |
| COM1 | COM1 | □ | 5BC | 5DP | 4E | 4D | 4C | 4DP | 3E | 3D | 3C | 3DP | 2E | 2D | 2C | 2DP | 1E | 1D | 1C | 1B |
| PIN | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 | 39 | 40 |
| COM1 | 1A | 1F | 1G | 2B | 2A | 2F | 2G | L2 | 3B | 3A | 3F | 3G | L1 | 4B | 4A | 4F | 4G | LOBAT | □ | COM1 |

NOTES:

- 1. Polarizer: Reflective
- 2. Display Module: TN, Positive
- 3. Viewing Direction: 6 O'CLOCK
- 4. Driving Condition: STATIC
- 5. Operating Voltage: 3.3 V
- 6. Operating Temp: -30°C TO +80°C
- 7. Storage Temp: -30°C TO +80°C
- 8. Connection: Pin