



Fuse, Dimensions: 6.3x32 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 500 / 440 V, Rated current: 0.8 A

#### **Business data**

Article number	<u>4978.0</u>
Article name	SI 6,3x32 0,800A-F
GTIN (EAN)	4044211109400
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	0.96 g
Weight per piece (including packaging)	1 g
Unit of weight	G
Customs number	85361010
Country of origin	EU
Product description	fuse



### **Technical data**

Dimensions		
Length	31.8 mm	
Diameter of contact cap	6.35 mm	
Dimensions	6,3x32 mm	
Ratings		
Rated voltage	500 / 440 V	
Rated current	0.8 A	
Materials		
Contact caps	Brass	
Surface	Nickel	
Tube	Ceramic	
Further technical data		
Trigger characteristic	Fast-acting (F)	
Rated breaking capacity	50 kA @ AC 500 (cos? = 0,3)	
Voltage drop	600 mV	
Power loss (@ 1.5 ln)	1.4 W	
Melting integral I <sup>2</sup> ts	0.49 A²s	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-01-17	
REACH Candidate Substance Note	No	
RoHS Conform	yes	

Media





Accessories