

Label for rough plastic surfaces - EML-HA (76X51)R SR - 0830620


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Label for rough plastic surfaces, Roll, silver, Unlabeled, Can be labeled with: Thermomark R, Thermomark X, Thermomark S, Mounting type: Adhesive, Lettering field: 76 x 51 mm

The figure shows a version of the article

Key commercial data

| | |
|----------------------|--|
| Packing unit | 1 PCE |
| GTIN |  4 046356 719742 |
| Custom tariff number | 39199000 |
| Country of origin | GERMANY |

Technical data

General

| | |
|-------------------------------------|--------------------------------|
| Length (b) | 76 mm |
| Width (a) | 51 mm |
| Color | silver |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Ambient temperature (operation) | -40 °C ... 150 °C |
| Ambient temperature (assembly) | 5 °C |
| Components | free from silicone and halogen |
| Material | Polyester |
| Number of individual labels | 1000 |
| Number of individual labels per row | 1 |
| RoHS compliant | Yes |
| Adhesive | Acrylic |
| Printability | Thermal transfer |
| Device | 5146477 THERMOMARK ROLL |
| Device | 5146723 THERMOMARK ROLL X1 |

Label for rough plastic surfaces - EML-HA (76X51)R SR - 0830620

Technical data

General

| | |
|--|---|
| Device | 5145274 THERMOMARK X1.1 |
| Device | 5146231 THERMOMARK X1.2 |
| Device | 5146257 THERMOMARK S1.1 |
| Ink ribbon | 5145384 THERMOMARK-RIBBON 110 |
| Ink ribbon | 0829544 THERMOMARK-RIBBON 110 BU |
| Ink ribbon | 0829542 THERMOMARK-RIBBON 110 GN |
| Ink ribbon | 0829543 THERMOMARK-RIBBON 110 RD |
| Test specification weathering-resistance | Following ISO 4892-2:2006-02 + A1:2009-07 |
| Test duration | 96 h |
| Wipe resistance test result | Test passed |
| Salt spray test specification | DIN EN ISO 9227:2012-09 |
| Test duration | 96 h |
| Salt spray testing result | Test passed |
| Alternating condensation climate with SO2 test specification | DIN 50018:1997-06 |
| Climate level | KFW 1.0 S |
| Cycles | 2 |
| Condensation test result | Test passed |
| Foil strength | 50 µm |
| Adhesive strength | 45 µm |

Classifications

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC000761 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 24190219 |
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27149103 |

Label for rough plastic surfaces - EML-HA (76X51)R SR - 0830620

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |

Accessories

Accessories

Ink ribbon - THERMOMARK-RIBBON 110 - 5145384



Ink ribbon, Length: 300000 mm, Width: 110 mm, Color: black